



[illegible]

SECRET CONT.D

STANDARD CATHODE

PLEASE DO NOT WRITE IN THESE SPACES

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

NEW 243 50 30 10 2001

[illegible]

DTIC NO. AD-764 115 PO 110  
(1 of 10 pages)

Spudded 12-4-61. Cemented 97 1/8 5/8" casing @ 104 1/2 w/60 sacks. Good circulation. WOC 12 hours. Commenced drilling 7 7/8" hole 12-5-61. Reached TD of 3935 12-9-61. Ran Schlumberger electric log. Cemented 3927 1/2", 9.5 lb/cu ft casing @ 3933 with 100 sacks. P.D. 3:30 A.M. 12-10-61. Moved rotary off to WOC. Perfected casing opposite Pictured cliffs and from 3846-94 with 2 jets per foot 1-8-62. Placed down casing with 40,000 gallons water and 40,000 sand. Shipped well in.

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of re-drilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or balling.

## HISTORY OF OIL OR GAS WELL

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE

[illegible]