

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
Robert L. Bayless

3. ADDRESS OF OPERATOR
P.O. Box 1541, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1130' FNL & 1130' FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
JUN 27 1983
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Pulled rods & tubing and reset. Details attached.

RECEIVED
JUN 29 1983
OIL CON. DIV.
DIST. 3

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert L. Bayless TITLE Operator DATE June 27, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

JUN 28 1983

NMOCC

FARMINGTON, N. M.
BY JK

ROBERT L. BAYLESS

PETROLEUM PLAZA BUILDING
P. O. BOX 1541
FARMINGTON, NEW MEXICO 87499
(505) 326-2659

Daily Report

Jicarilla 118 A #1
1130' FNL & 1130' FEL
Sec. 26, T26N, R3W
Rio Arriba County, New Mexico

6-22-83 Pulled 155 5/8" rods & pump. (51 plain rods & 104 scraped rods). Add 42.07' of tubing and tagged bottom. Pulled tubing and tallied out of hole. Pulled 124 jts of 2-3/8" tubing (3910.33') (bottom at 3997'). Well originally landed as follows:

<u>DEPTH</u>	<u>DESCRIPTION</u>	<u>LENGTH</u>
0-12	KB to landing point	11.90
12-3922	124 jts 2-3/8" J-55 EUE tubing	3910.33
3922-3923	1 seating nipple	.75
3923-3929	1 perforated sub	6.00
3929-3960	1 mud anchor	31.15
		<u>3960.13</u>

Rigged up sand pump. Recovered sand and sludge from well. Recovered oil and water as fluids. Tripped in hole with tubing. Tagged bottom at 3996'. Landed tubing as follows:

<u>DESCRIPTION</u>	<u>LENGTH</u>	<u>DEPTH</u>
KB to landing point	11.90	0-12
125 jts 2-3/8" 4.7#/ft. J-55 EUE tubing	3942.24	12-3954
1 seating nipple	.75	3954-3955
1 perforated sub	6.00	3955-3961
1 mud anchor	31.15	3961-3992
	<u>3992.04</u>	

SDFN.

6-23-83 Ran 5/8" rods and pump and spaced out as follows:

<u>DESCRIPTION</u>	<u>LENGTH</u>	<u>DEPTH</u>
KB to landing point	10.00	0-10
Polished rod 1 1/4" X 16' with 1 1/2" liner	16.00	10-26
5/8" rod subs	6.00	26-32
52 5/8" regular rods	1300.00	32-1332
104 5/8" scraped rods	2600.00	1332-3932
Pump 2" X 1 1/2" X 16' (bottom hold down)	16.00	3932-3948
	<u>3948.00</u>	

Wait on pumper to work on pumping unit engine. Released rig.