



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Santa Fe**  
Lease No. **079285**  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO <del>REPAIR</del> CASING	<input checked="" type="checkbox"/>	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Inter-South Penn Duro UBL

May 3, 1960

Well No. **#1-27** is located **660** ft. from **{N}** line and **1980** ft. from **{E}** line of sec. **27**  
**NE/4 of NW/4** **26 N., R. 1 E.** **N.M.P.M.**  
(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Puerto Chiquita** **Rio Arriba** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **7301** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run logs at T.D. 2563'. Plug back with sand stone to 2591' plus 1 sk Calseal to 2587'. Prep to run and cement 5 1/2" casing in dry hole at 2587' and test by hydrofracing oil show from fractured shale at 2600' - 2663'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **INTEX OIL COMPANY**  
Address **P.O. Box 1411**  
**Bakersfield, Calif.**  
**PA 4-4956**  
By **R. S. Miller**  
Title **Production Manager**