

*Post as
P & A*

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079266
Unit Vaughn

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	X
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 4, 1954

Well No. 2 is located 1150 ft. from N line and 1010 ft. from W line of sec. 20
Section 20 26N 6W MM
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
So. Blanco P.C. Hic Arriba New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 645 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

September 24, 1954, attempted to recompleate in Kirtland formation. Set Lane Wells bridging plug at 2620'. Dumped 400# of Hydromite on top of plug. Top of Hydromite plug at 2583'. Perforated w/L.W. 2 each A-2 bulletts from 2130' to 2105', slight blow of air for 10 minutes and died. Water level found in casing at 150', swabbed for one hour. Approximately 200' of water was swabbed each run. Water level remained at 150'. Water was fresh, and producing approximately 6,000 gallons per hour.

Second L.W. bridging plug was set at 1875' with 400# Hydromite dumped on top. Top of Hydromite at 1835'.

9-25-54, Dia-log jet cutters run in and shot casing at 1778'. Pulled a total of 56 joints 5 1/2" casing (1781').

(Over)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company


Address Box 997

Farmington, New Mexico

By 

Petroleum Engineer

Title



9-26-54 Removed broken head and packed 50 sacks cement in the 9 5/8 casing from 90' elevated to surface. A short joint of 4" pipe was placed on top with well name, location for a permanent marker.