

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports

95 MAY 10 AM 7:38

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1180' FSL, 1840' FWL, Sec. 20, T-26-N, R-6-W, NMPM

5. Lease Number
SF-079302A
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Sanchez A #1
9. API Well No.
30-039-06361
10. Field and Pool
Blanco Pictured Cliffs
11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

5-3-95 MIRU. ND WH. NU BOP. POOH w/94 jts 1 1/4" tbgs. TIH w/5 1/2" gauge ring to 2950'. TOOH. TIH w/5 1/2" cmt retainer, set @ 2918'. PT tbgs to 1200 psi, OK. Load hole w/66 bbl wtr. Attempt to PT csg, failed due to leaking WH. Establish injection. Plug #1: pump 14 sx Class "B" cmt below cmt retainer into Pictured Cliffs perfs & 86 sx Class "B" cmt above cmt retainer to 2159'. POOH. SDON.

5-4-95 TIH, tag cmt @ 2240'. Perf 4 sqz holes @ 788'. Load hole w/6 bbl wtr. Could not establish injection into perfs. (Verbal approval to change plans approved by Ron Snow, BLM). TIH w/tbgs to 838'. Plug #2: pump 23 sx Class "B" cmt inside csg @ 635-838'. TOOH. TIH to 180'. Perf 4 sqz holes @ 177'. Pump 80 bbl wtr to establish circ. Would not circ out bradenhead. Pump 20 more bbl wtr, no circ or blow. Plug #3: pump 119 sx Class "B" cmt @ 0-177'. Circ 1 bbl cmt out bradenhead. SDON.

5-5-95 ND BOP. Cut off WH. Found cmt in 5 1/2" csg & surface csg annulus down about 70'. Pump 20 sx Class "B" cmt to fill csg. Install dry hole marker w/4 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 5-5-95.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 5/9/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

APPROVED

MAY 10 1995

NMOCD

DISTRICT MANAGER