(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42–R350 Approval expires 12–31–60.	X.
Indian Agency	1-0-4
Contract / 17	
Allottes Track 190	
. Manual 11a war	

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING	supplementary well history
NOTICE OF INTENTION TO ABANDON WELL	U. S. GRULDGICAL SUI
	SCK MARK NATURE OF REPORT, NOTICE OR OTHER DATA)
(INDICATE ABOVE BY CHE	ICK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
<i>*</i> •	Mark and the second
•	
diserille "9"	The second secon
ell No is located	ft. from line and ft. from line of sec.
المساورين	TOTAL
(14 Sec. 200 Sec. No.) (Twp.)	(Hange) (Meridian)
A	La Samelha
(Jiad)	(County or Subdivision) (State or Territory)
Ange Rata	
e elevation of the derrick floor above	e sea level is Call tt.
•	
	DETAILS OF WODE
	DETAILS OF WORK
	DETAILS OF WORK s; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- s, and all other impertant proposed work)
ter setting 296° of 10-3/4° inserts. Circulated, Tested May 30 minutes before and after	
ter setting 296° of 10-3/4° inserts. Circulated. Sected Market and after 10 minutes before and after 1 understand that this plan of work must receive a	s; show size, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) Synface Casing on bottom at 276° with 250 cm. 3-1/4" Supface Casing on bottom with 300 for drilling First. Tested CK. No Synch. Spread of the Company of the Comp
ter setting 296° of 10-3/4° impoints to objective sand ing points ing points and setting 296° of 10-3/4° imposes. Captulated, Section 20 minutes before and after 1 understand that this plan of work must receive a	s; show size, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) Synface Casing on bottom at 276° with 250 cm. 3-1/4" Supface Casing on bottom with 300 for drilling First. Tested CK. No Synch. Spread of the Company of the Comp
Ther setting 296° of 10-3/4° in points and ing points are setting 296° of 10-3/4° in points and after and after and after and after a set and a set an	s; show size, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) Synface Casing on bottom at 276° with 250 cm. 3-1/4" Supface Casing on bottom with 300 for drilling First. Tested CK. No Synch. Spread of the Company of the Comp
Ther setting 296° of 10-3/4° in points of the setting 296° of 10-3/4° in present. Section is a set of the set	s; show size, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) Synface Casing on bottom at 276° with 250 cm. 3-1/4" Supface Casing on bottom with 300 for drilling First. Tested CK. No Synch. Spread of the Company of the Comp
Ther setting 296° of 10-3/4° company NACE CLA FERENCE COMPANY AND ADDRESS OF SOLUTION OF S	s; show size, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) Synface Casing on bottom at 276° with 250 cm. 3-1/4" Supface Casing on bottom with 300 for drilling First. Tested CK. No Synch. Spread of the Company of the Comp

Signature of the second of the and the second second of the second s