
(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Indian Agency	learilla
Allottee Jicapii	la Tribal
Losse No. Contro	et 109

	SUBSECUENT DEPORT OF WATER SHITLOFF
CE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHOT-OT-
CE OF INTENTION TO CHANGE PLANS.	
CE OF INTENTION TO TEST WATER SH	
CE OF INTENTION TO REDRILL OR RE CE OF INTENTION TO SHOOT OR ACID	
CE OF INTENTION TO PULL OR ALTER	
ICE OF INTENTION TO ABANDON WELL.	
A THE CONTRACT OF THE CONTRACT	
(INDICATE ABO	ove by check mark nature of report, notice, or other data)
,	·
•	
	(NI)
No is located	d 1460 ft. from $\stackrel{[N]}{=}$ line and 305 ft. from $\stackrel{[M]}{=}$ line of sec. 2
4 MM/4 Sec. 21	26 N 5 N N , N , P , N ,
()4 Sec. and Sec. No.)	(Twp.) (Reange) (Meridian)
Blanco PC Ext.	Rio Arriba New Mexicon
(Field)	(County or Subdivision) (State of Particety)
alaryation of the derrick floo	or above sea level is 6554 ft.
elevation of the defrick hoo	
	DETAILS OF WORK OIL CON. COM.
	cation and a character variable and langths of proposed casings, indicate with Clints can
names of and expected depths to obje	ective sands; show sizes, weights, and lengths of proposed casings; indicate military is in ing points, and all other important proposed work)
names of and expected depths to obje	ective sands; show sizes, weights, and lengths of proposed casings; indicate mustare jets, center ing points, and all other important proposed work)
names of and expected depths to obje	ective sands; show sizes, weights, and lengths of proposed casings; indicate mustare jets, center ing points, and all other important proposed work)
6-29-57 70 3111'	ective sands; show sizes, weights, and lengths of proposed casings; indicate mustare lieur, centuring points, and all other important proposed work)
6-29-57 70 3111'	ective sands; show sizes, weights, and lengths of proposed casings; indicate minimalies, con in ing points, and all other important proposed work) HKB. Set 31 joints 3108; of 5-1/2" 00
6-29-57 70 3111'	ective sands; show sizes, weights, and lengths of proposed casings; indicate minimalists; comming points, and all other important proposed work) HKB. Set 31 joints 3108; of 5-1/2" 00 -55 casing at 3110; BKB with 100 sacks
6-29-57 70 3111'	HKB. Set 31 joints 3108; of 5-1/2° 00 -55 casing at 5110; BKB with 100 sacks Temperature survey should top of ocusent
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Pressur	HKB. Set 31 joints 3108' of 5-1/2" OD -55 easing at 3110' BKB with 100 sacks Temperature survey should top of cement
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Pressur	HKB. Set 31 joints 3108; of 5-1/2° 00 HKB. Set 31 joints 3108; of 5-1/2° 00 -55 casing at 3110; BKB with 100 sacks Temperature survey showed top of cement red up on casing to 1000%. No pressure in one hour.
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Pressur	HKB. Set 31 joints 3108; of 5-1/2° 00 HKB. Set 31 joints 3108; of 5-1/2° 00 -55 casing at 3110; BKB with 100 sacks Temperature survey showed top of cement red up on casing to 1000%. No pressure in one hour.
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Pressur	HKB. Set 31 joints 3108; of 5-1/2" o
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Pressur	HEB. Set 31 joints 3108; of 5-1/2" o
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Pressur	HEB. Set 31 joints 3108; of 5-1/2" o
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Pressur decrease	HKB. Set 31 joints 3108; of 5-1/2" on -55 casing at 3110; BKB with 100 sacks Temperature survey should top of occupant red up on casing to 1000. He pressure in one hour. RECEIVEL AUG 5 1957
6-29-57 TD 3111' 15.56 J- cement. at 2450' 7- 1-57 Pressur degrees	HKB. Set 31 joints 3108' of 5-1/2" o
6-29-57 TD 3111' 15.56 J- cement. at 2450' 7- 1-57 Pressur degrees	HEB. Set 31 joints 3108; of 5-1/2" o
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Procesur degreeses nderstand that this plan of work must	HKB. Set 31 joints 3108' of 5-1/2" o
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Procesur decrosses	HKB. Set 31 joints 3108' of 5-1/2" o
6-29-57 TD 3111' 15.5# J- cement. at 2450' 7- 1-57 Procesur degreeses nderstand that this plan of work must	HKB. Set 31 joints 3108' of 5-1/2" o



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency	Jicarilla
---------------	-----------

Allottee Jicarilla Tribel

Lease No. __Contract 109

SUNDRY NOTICES AND REPORTS ON WELLS

	W TO DOUG		H			1	ì
	N TO DRILL		SUBSEQUENT R	EPORT OF WATER	SHUT-OFF		
	N TO CHANGE PLANS		SUBSEQUENT R	EPORT OF SHOOT	ING OR ACIDIZING	·	
NOTICE OF INTENTIO	N TO TEST WATER SHUT-C	OFF	SUBSEQUENT F	EPORT OF ALTERI	NG CASING		
	N TO REDRILL OR REPAIR	WELL	1		LING OR REPAIR.		
	N TO SHOOT OR ACIDIZE		H	EPORT OF ABAND			
	N TO PULL OR ALTER CAS	ing	1	Y WELL HISTORY		44	
OTICE OF INTENTIO	ON TO ABANDON WELL		- prpeda	ent velo	- OI - BE	1011.00-	
	(INDICATE ABOVE B	Y CHECK MARK N	ATURE OF REPORT	NOTICE OF OTHER	DATA)	} (
	(MBIGHTE ABOTE D	TO LEGIC MARKET	ATORE OF REPORT,	NOTICE, OR OTHER	L DATA,		
				Ansanant Ti	o <u>\$</u>	10	67
		•				17	-34
			(N)		# 1		
ell No 🏂	is located 1	460_ft. from	n 🚰 line and	.905ft. fr	om $\{W\}$ line	of sec	1
man de same de		<u> </u>	(1444)		(**)		
(34 Sec. and Se		26¥	(Range)	(Meridian)		and the second	
	PC Ext.	1 44.	Arriba	(maidian)	Manage Manager		
(Field)	IV ABY:	(County or	Subdivision)		(State or Terris	72-11-	i . A
		• •					
ne elevation of	the derrick floor a	bove sea leve	l is 655% f		1 "	106	7 🚺
					1 A	υ α 6 195	
	spected depths to objective lng ;	DETAIL	S OF WORK			SON C	OM. [
ate names of and ex	pected depths to objective	sands; show sizes,	, weights, and leng	hs of proposed car	ings; indicate (1)	dding johe-ced	ent-
	ing	points, and all oth	er important prop	osed work)		DIS1.	· /
					•		40
7-1-57	TD 5111' REB		ed out t		Perform		
	TD 5111' RKB 3006-3043' a		الماسية المساهدة	30901.	Perfore	ited	
	TD 3111' RKB 3008-3043' as		ed out t	30901.	*****	ited	
	TD 5111' RKB 3008-3043' as Sandfraced w		ed out t	30901.	Perfore	ited	
	TD 5111' RKB 3008-3043' a Sandfraced w sand, flumber 160 mubber b		ed out t	30901.	Perfore	ited	
	TD 3111' RKB 3008-3043' a Sandfraced w sand, flushe 160 rubber b		ed out t	o 30901. h 4 holes s water : ems water during	Perfore	ited	
	TD 5111' RKB 3008-3043' a Sandfraced w sand, flusher 160 rubber b Breakdown pr	. Cleand nd 3062- ith 24,8 d with 3, alls in 1 essure 2	ed out to 5078' with 10 gallon ,200 gallon 1500, tru	30901.	Perfore	ited it. iod it.	
	TD Jill' RKB 3006-3043' a Sandfraced w sand, flushe 160 rubber h Breakdown pr 1800/, avera		ed out to 5078' with 10 gallon ,200 gallon 1500, tru	o 30901. h 4 holes s water : ems water during	Perfore	ited it. iod it.	
7-1-57	TD 5111' RKB 3008-3043' a Sundfraced w sand, flushe 160 rubber b Breakdown pro 1800/, avera	Cleand 1 3052- 1 th 24,8 4 with 3 1 le in 1 sesure 2 1 ject	ed out to 5078' with 100 gallon, 200 gallon stage 1506, tree ion rate	o 30901. h 4 holes s water s ems water s during sting pro-	Perford per for me 30,00 r. Brogg treatmen meure 15	it.	in Section Sec
7-1-57	TD 5111' RKB 3008-3043' a Sandfraced w sand, flusher 160 rubber b Breakdown pr	Cleand 1 3052- 1 th 24,8 4 with 3 1 le in 1 sesure 2 1 ject	ed out to 5078' with 100 gallon, 200 gallon stage 1506, tree ion rate	o 30901. h 4 holes s water : ems water during	Perford per for me 30,00 r. Brogg treatmen meure 15	it.	in the second se
7-1-57	TD 5111' RKB 3008-3043' a Sundfraced w sand, flushe 160 rubber b Breakdown pro 1800/, avera	Cleand 1 3052- 1 th 24,8 4 with 3 1 le in 1 sesure 2 1 ject	ed out to 5078' with 100 gallon, 200 gallon stage 1506, tree ion rate	o 30901. h 4 holes s water s ems water s during sting pro-	Perford per for me 30,00 r. Brogg treatmen meure 15	it.	in the second se
7-1-57	TD 5111' RKB 3008-3043' a Sundfraced w sand, flushe 160 rubber b Breakdown pro 1800/, avera	Cleand 1 3052- 1 th 24,8 4 with 3 1 le in 1 sesure 2 1 ject	ed out to 5078' with 100 gallon, 200 gallon stage 1506, tree ion rate	o 30901. h 4 holes s water s ems water s during sting pro-	Perford per for me 30,00 r. Brogg treatmen meure 15	it.	in the second se
7-1-57 7-2-57	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to some out to gallon, 200 gallon stage 150%, true stage to gallon sate ag 2,054	o 30901. h 4 holes s water s ems water s during sting pro 60.4 hs	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-1-57 7-2-57	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to some out to gallon, 200 gallon stage 150%, true stage to gallon sate ag 2,054	o 30901. h 4 holes s water s ems water s during sting pro 60.4 hs	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-2-57	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to some out to gallon, 200 gallon stage 150%, true stage to gallon sate ag 2,054	o 30901. h 4 holes s water s ems water s during sting pro 60.4 hs	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-2-57	TD 5111' RKB 3008-3043' a Sundfraced w sand, flushe 160 rubber b Breakdown pro 1800/, avera	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to some out to gallon, 200 gallon stage 150%, true stage to gallon sate ag 2,054	o 30901. h 4 holes s water s ems water s during sting pro 60.4 hs	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-2-57 I understand that tompany	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to some out to gallon, 200 gallon stage 150%, true stage to gallon sate ag 2,054	o 30901. h 4 holes s water s ems water s during sting pro 60.4 hs	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-2-57	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to some out to gallon, 200 gallon stage 150%, true stage to gallon sate ag 2,054	o 30901. h 4 holes s water s ems water s during sting pro 60.4 hs	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-2-57	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to sold out to sold out to stage allow stage st	o 30901. h 4 holes b water s per water s during bting pro 60.4 hr	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-2-57	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to sold out to sold out to stage allow stage st	o 30901. h 4 holes s water s ems water s during sting pro 60.4 hs	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC
7-2-57	TD J111' REB 3008-3043' a Sandfraced w sand, flusher 160 rubber h Breakdown pro 1800/, avera After 12 hou	Cleand nd 3062-; ith 24,80 d with 3, alls in 1 essure 2: go inject re flowin	ed out to sold out to sold out to stage allow stage st	a 30901. h 4 holes h water a has water s during sting pro 60.4 mm 1007/day.	Perform per for med 30,00 r. Brogg treetmen 15.	ISON INC.	WEXIC

· -