Form 9-331 b (April 1952)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Budget Bureau No. 42-R359.4. Approval expires 12-31-60. Indian Agency ... JIGAT1110

Allotte Jicarilla Apache Lease No. Contract 110

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO REDRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL.	 SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT. SUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK MANNE	

e by check mark nature of report, notice, or other data) July 5th _____, 19<u>__</u>57 Well No. 6-3 is located 990 ft. from $\begin{bmatrix} N \\ 2 \end{bmatrix}$ line and 990 ft. from $\begin{bmatrix} 13 \\ W \end{bmatrix}$ line of sec. 20 S. Blanco PC Ext. Nio Arribe New Mexico (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 6617 ft. **DETAILS OF WORK** (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) Cleaned out to 3110'. Perforated 3030-3056' and 3070-3092' with 4 holes per foot. Sandfraced with 26,000 gallons water and 30,000 sand, flushed with 3,200 gallons water. Breakdown pressure 3000, treating pressure 1550, average injection rate 58 BPM. Disped 160 rubber balls in two stages during 6- 7-57 treatment. After 16 hours flowing 1,065 MCF/day. 6- 8-57 ± 01.9 CIL CON. COM I understand that this plan of work must receive approval in writing by the Geological Survey Company EL PASO NATURAL GAS COMPANY Address Box 997 Parmington, New Muxico

U. S. GOVERNMENT PRINTING OFFICE 16-8437b-8