

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Caulkins Oil Company
3. ADDRESS OF OPERATOR
P.O. Box 780, Farmington, New Mexico
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' F/S 1660' F/E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input checked="" type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)	set 2 7/8" liner		

5. LEASE
NM-03554
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Breech C
9. WELL NO.
301
10. FIELD OR WILDCAT NAME
South Blanco PC
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 14 26N 6W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6673' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD-3175 Completed drilling 7-3-52.
7-3-52 5 1/2" 17# H-40 casing cemented at 3068' with 200 sacks.
7-25-52 Shot with 665 qts. SNG 3078' to 3175'.
7-25-52 Cleaned out to 3075'. Gas gauged 1909 MCFPD.
5-12-57 Sand water frac'ed with 42,000# sand and 31,920 gals. water.
Daily volume to pipeline after treatment 927 MCFPD.
10-20-77 Daily volume now has decreased to 115 MCFPD. to pipeline. It is now proposed to clean out well to 3175' and then cement 2 7/8" liner from approx 2968' to 3175'. Liner will then be perforated opposite PC sand and frac'ed with 50,000# sand. A small pit on existing location will be required to contain frac water after frac job. After job is completed, disturbed area will be cleaned up and then reseeded to 5' of facilities. Est. starting date July 15, 1979.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles Dugan TITLE Superintendent DATE March 20, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 26 1979

U. S. GEOLOGICAL SURVEY
DORANGO, COLO.