MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Duration of Flow
Oh5! Ss. 12 psia O. Dual Duration of Flori
Duration of Flor
Duration
Duration
Duration of Flo
Duration of Flo
Duration of Flo
of Flo
of Flo
i Um
111.
3 Hours
Rate of Flow
Q-MCFPD @ 15.025 psi
@ 15.025 psi
6,86);.0
rator Gas_ ving Fluid_O.(
P _W P _C
ED
ED 1956

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_w) . MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{w}}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_{W} cannot be taken because of manner of completion or condition of well, then P_{W} must be calculated by adding the pressure drop due to friction within the flow string to $P_{t,i}$

OfL CONSERVATION COMMISSION

AZTEC OSTOCT OFFICE

No. Copies Received

DISTRIBUTION

NO.
FURNISHED

Operator

Santa Fe

Proration Office

State Land Offica

U.S.G.S.

Transporter

File