STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

erator		BIL PRODUCIN	G TX. & N.M.	INC. Lease	<u>Jicarilla D</u>		Well No2		
			r 26N	Rae	03W —	County	Pio_Aribba		
Well: 1	Unit A Sec. 14 Twp. 26N			TYPE OF PE	ROD.	ETHOD OF PROD. (Flow or Art. Lill)	PROD. MEDIUI (Tbg. or Csg.)		
Upper mpletion	Gavi]	lan Pictured		Gas	as Flow		TBG		
Lower mpiation	mer .		Gas	Gas Flow		TRG			
			PRE-FLO	OW SHUT-IN P	RESSURE DATA	· · · · · · · · · · · · · · · · · · ·			
Hour, date shut-in		hut-in	t-in Length of time shut-in		SI press. psig		Stabilized? (Yes or No)		
mpletion		11-9-91		3 days		Str	Stabilized? (Yes or No)		
Lower empletion	Hour, date s	12-1-91	1 yr.		Si press. paig		Ves		
premon	<u> </u>	<u> </u>	1 7 4 9				•		
		11 1/ 0	1	FLOW TEST	NU. 1 Zone producing (Up	per or Lowert LO	WER		
TIME LAPSED TIME Upper Completion		SURE	PROD. ZONE	REMARKS					
			Upper Completion	Lower Completion	TEMP.	<u> </u>	VEWAUVA		
11-1	5-91	lst day	381	300#	date	111.65.701	Lt. (30 – 13 – 91		
11-16	6-91	2nd day	353	300#	upper	404#	404#		
					lower	.300#	300#		
					14	To M CAR	N CAS & Primary		
	 ;					 			
roducti	ion rate d	luring test		<u> </u>					
			D based on	Bbls. i	in Hour		av GOR _		
325:	60				u (Orifice or Mete				
	How date	shui-in	MID-T		PRESSURE DATA	s	Stabilized? (Yes or No)		
Upper completion Hour, date shul-in Length of lim Hour, date shul-in Length of lim						Stabilized? (Yes or No)			

FLOW TEST NO. 2

Zone producing (Upper or Lower):

TIME	LAPSED TIME	PRESSURE		PROD. ZONE		
(hour, dete)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS	
				•	The second of th	
	•			·		
oduction rate di					<u>-</u>	
l:	ВОР	D based on	Bbls. in	Hours.	Grav GOR	
s:		MCF	D: Tested thru	(Orifice or Meter):		
marks:			······································		• • • • • • • • • • • • • • • • • • •	
ereby certify th:	at the informati	on herein containe	d is true and con	aplete to the best	of my knowledge.	
proved	JEC 3 0 19	191	_ 19 O		IL EXP. & PROD. U.S. INC.	
vew, Mexico Oii	Conservation D	Division	Ву	199	Hoyd	
Origin	nal Signed by CH/	ARLES GHOLSON	Ti	ele PRODUC	CTION TECH. I	
c DEPUTY OF	L & GAS INSPECT	ror, dist. #3	Da			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the rubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) 中中

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven glays in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packet leakage test, a gas well is being flowed to the authosphere due to the lack of a gipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced 200e shall remain shut-in while the 200e which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

