## NEW MEXICO OIL CONSERVATION COMMISSION

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Cil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIFING WELL			
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL  REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON PULLING OR OTHERWISE			
		ALTERING CASING REPORT ON DEEPENING WELL			
					REPORT ON RESULT OF PLUGGING OF V
9.0	entamban O	1060			
	eptember 9	Date	Farmington, N	OW MOXIC	
72 V		under the beadings	atad abas a stalle		
Following is a report on the work done and th  Caulkins Oil Company		_			
Company or Operator		Lease			
Northwest Quarter of Sec.					
PcolPcol		R10	Arriba	Count	
The dates of this work were as follows:					
Notice of intention to do the work was	P= 127 1	T 0100	Assessment 1	10 6	
7-60 - TD - 7650'. 3-60 - Ran Schlumberger In 9-60 - Ran 5" OD,15# casin	INT OF WORK Iduction, Ig 0 to 2	done and resul Gamma Ray an 957 and 45"	ATS OBTAINED  IN TEMPERATURE 1  OD. 11.6# cas	ing 2957	
7-60 - TD - 7650 .	int of work iduction, ig 0 to 2 through shouts per collars 1987.	Gamma Ray an 957 and $\frac{1}{2}$ oe with 200 sack, plus 5 were used in 3300 and 3	of Temperature 1 OD, 11.6# cas sacks 12% Bent to the 42 portion 10.38 and that	ing 2957 onite cer cement. on of the	
7-60 - TD - 7650'.  3-60 - Ran Schlumberger In  3-60 - Ran 5" OD,15# casin to 7644'. Cemented t Containing 12½# Gilso Multi-stage cementing string at 3290' and 2  3-60 - ½" casing was perf the 4½" casing was ce	int of work iduction, ig 0 to 2 through shouts per collars 1987.	Gamma Ray an 957 and $4\frac{1}{2}$ oe with 200 sack, plus 5 were used in 3300 and 3 th 75 sacks.	od Temperature of OD, 11.6# cas sacks 12% Bent to sacks Latex the 4½ portion of the 4½ and that	ing 2957 onite cercement. on of the portion	
DETAILED ACCOUNTS.  7-60 - TD - 7650'.  8-60 - Ran Schlumberger In  9-60 - Ran 5" OD,15# casin  to 7644!. Cemented t  Containing 12½# Gilso  Multi-stage cementing  string at 3290' and 2  8-60 - 4½" casing was perf  the 4½" casing was ce	int of work iduction, ig 0 to 2 through shouts per collars 1987.	Gamma Ray an 957 and $\frac{1}{2}$ oe with 200 sack, plus 5 were used in 3300 and 3	od Temperature of OD, 11.6# cas sacks 12% Bent to sacks Latex the 4½ portion of the 4½ and that	ing 2957 onite cercement. on of the portion	
DETAILED ACCOUNTS.  -60 - TD - 7650'.  -60 - Ran Schlumberger In -60 - Ran 5" OD,15# casin to 7644'. Cemented t Containing 12½# Gilse Multi-stage cementing string at 3290' and 2  -60 - ½" casing was perf the 4½" casing was ce	unt of work  iduction,  ig 0' to 2  chrough shoults per  collars  987'.  orated at  mented wi	Gamma Ray an 957' and 42' oe with 200 sack, plus 5 were used in 3300' and 3 th 75 sacks.	on 11.6# cas sacks 12% Bent to sacks Latex the 42 portion of the first p	ing 2957 onite cer cement. on of the	
DETAILED ACCOUNTS.  7-60 - TD - 7650'.  8-60 - Ran Schlumberger In  8-60 - Ran 5" OD,15# casin  to 7644'. Cemented t  Containing 12½# Gilse  Multi-stage cementing  string at 3290' and 2  8-60 - ½" casing was perf  the 4½" casing was ce	int of work iduction, ig 0' to 2 chrough shi inte per collars 987'. orated at mented wi	Gamma Ray an 957' and 42' oe with 200 sack, plus 5 were used in 3300' and 3 th 75 sacks.	on 11.6# cas sacks 12% Bent to sacks Latex the 42 portion of the first p	ing 2957 onite cer cement. on of the	
DETAILED ACCOUNTS.	int of work iduction, ig 0' to 2 chrough shoulte per collars 2987'. crated at mented wi	Gamma Ray and 957 and 12 oe with 200 sack, plus 5 were used in 3300 and 3 th 75 sacks.  Company  I hereby swear of is true and confect Name.	on 11.6# cas sacks 12% Bent to sacks Latex the 42 portion of the first p	ing 2957 onite cer cement. on of the portion of	
DETAILED ACCOUNTS.  DETAILED ACCOUNTS.	int of work iduction, ig 0' to 2 chrough shi inte per collars 987'. orated at mented wi	Company  Com	ad Temperature of OD, 11.6# cas sacks 12% Bent to sacks Latex the 4½" portion of the temperature of the 4½" portion of the temperature of temperature o	ing 2957 onite cer cement. on of the portion of	

9-

	STATE OF NEW A	MEXICO			
	OIL CONSCRIVATION C	JMM:SSIC	1.2		
	AZI C DISTRICT	OFFICE			
	NUMBER OF COPIES RECEIVED		3		
	D.\$1.35-2-0	CN			
7	SOMA FELT TO NELL	18351	gic tue	i聲的特 ·	
	Fig.	-/-			
	U.S.G.3.	ننظ.	and an	***:4:00 E	
	LAND OFFICE	-	<del>-</del>		
	TRANSPORTER OIL	-			
	PROBATION OFFICE	144			
	OPERATOR	1			

,

ę v