

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE. If State Land submit 5 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

CAULKINS OIL COMPANY
(Company or Operator)

STATE "A"
(Lease)

Well No. 2-233, in 14 $\frac{1}{4}$ of SW $\frac{1}{4}$, of Sec. 16, T. 26N, R. 6E, NMPM.

South Platte Pool, Pio Apache County.

Well is 200 feet from West line and 1145 feet from North line

of Section 16. If State Land the Oil and Gas Lease No. is R-293-23

Workover Commenced 2-23, 19 60 Workover was Completed 9-23, 1960

Name of Drilling Contractor Flow-er Drilling Company

Address 271 Meadows Building, Dallas 6, Texas

Elevation above sea level at Top of Tubing Head 6697 C.L. The information given is to be kept confidential until _____, 19____.

TOPS OF OIL SANDS OR ZONES

No. 1, from Pictured Cliffs 3035 No. 4, from Greenhorn xx 7188
No. 2, from Cliff House 4740 No. 5, from Graneros Shale 7243
No. 3, from Point Lookout 5370 No. 6, from Dakota xx 7273
No. 3, from Thicket xx 6003

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10 3/4"	40.5	Used	540'				Surface
7"	20	New	3038'				Production
5"	13	New	0-2937'		0-2931'	History Attached	
4 1/2"	11.6	New	2937'-7644'	Per.			Production

*Already in well

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13"	10 3/4"	540'	230			
8 3/4"	7"	3038	200			
6 1/2"	5"	2937	374			
6 1/2"	4 1/2"	7644				

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation _____

Depth Cleaned Out _____



RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 3125 feet to 7650 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Aahy	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Permian
T. Glorieta	T.	T. Permian
T. Drinkard	T.	T. Permian
T. Tubbs	T.	T. Penn.
T. Abo	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
3125	3155	30					
3155	4660	1505	Sand & Shale				
4660	4750	90	Shale				
4750	5362	600	Sand, Shale & Coal				
5362	7430	2068	Sand & Shale				
7430	7650	220	Sand				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator. Caulkins Oil Company Address. Box 760, Farmington, New Mexico
Name. Title. Field Superintendent