

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 02554

Unit Derrick "C"

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|--|--|-------------------------------------|
| NOTICE OF INTENTION TO DRILL | | SUBSEQUENT REPORT OF WATER SHUT-OFF | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 14, 1959

Well No. 10-244 is located 990 ft. from [N] line and 990 ft. from [E] line of sec. 14
14 26N 6W 104TH
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
South Blanco Rio Arriba New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6616 ft. S.L.


DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded at 6 P.M. 8-12-59.

Cemented 254' of 10 3/4" 32.75# H-40 casing at 267' w/200 sacks common cement, 1% Calcium Chloride. Cement circulated. Plug down at 12 P.M. (noon) 8-13-59.

8-14-59 - Casing tested w/800# for 30 minutes. Held ok.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Quilkins Oil Company

Address Box 967
Fernington, New Mexico

By Charles Ferguson
 Title Production Foreman