



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 03554
Unit _____
1 rooch "C"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 22, 1959

Well No. 40-244 is located 990 ft. from [N] line and 990 ft. from [E] line of sec. 14

36N 6W N40W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
South Blanco El Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6616 ft. C.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)
Drilled to TD 7616' 9-12-59, ran Induction Electrical Log & Sonic Log.
9-14 - Ran 5 1/2" OD J-15 Bnd 13.5' Casing 0 to 6587' and 5 1/2" OD J-15 Bnd
17' Casing 6587' to 7616 with equipment as follows:

Scratchers	Centralizers	BY Tools
7616 - 7231	7393	3616
6810 - 6770	7530	3212
3612 - 3280	7443	
6770 - 6700	7337	
3130 - 3030	7274	
	7231	

Cemented through shoe w/300 sacks 50% cement 50% pozmix plus 2% Howocel and 12% Wilsonite per sack. Used 30 sacks next as last of batch. Cemented through stage collar = 3616' w/264 sacks 50% cement 50% pozmix plus 2% Howocel & 12% Wilsonite per sack. Plug down = 9:30 PM 9-14.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. (over)

Company Caulkins Oil Company

Address Box 967

Armington, New Mexico

By Frank Gray

Title Field Superintendent

Running Temperature Survey on last stage. Casing rotated during both stages.

9-15 - Cemented through stage collar @ 3212' w/173 sacks cement. Plug down at 9 A.M. 9-15-59.