Dec. 1973	UNITED STATES	5. LEASE
	RTMENT OF THE INTERIOR	NM 03554
	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS		7. UNIT AGREEMENT NAME
(Do not use this form for	proposals to drill or to deepen or plug back to a different	8. FARM OR LEASE NAME
reservoir. Use Form 9-331-	-C for such proposition	Breech C
1. oil gas	☑ other	9. WELL NO.
Well Comment		248
2. NAME OF OPERATOR		10. FIELD OR WILDCAT NAME
Caulkins O	il Company	Blanco Mesa Verde-Basin Dakota
3. ADDRESS OF OPERATOR		11. SEC., T., R., M., OR BLK. AND SURVEY OR
P.O. Box 780 Farmington, New Mexico		AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17		Section 13 26 North 6 West
below.)		
AT SURFACE: 1140' From North and 900' From East AT TOP PROD. INTERVAL: same		Rio Arriba New Mexico
AT TOTAL DEDTU		14. API NO.
		24. /11 110.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OI	HER DATA	1
THE PART OF ARREST	OVAL TO: SUBSEQUENT REPORT OF:	6532 KB
REQUEST FOR APPR		
TEST WATER SHUT-		
FRACTURE TREAT SHOOT OR ACIDIZE		
REPAIR WELL	sing JUL 28	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CA	sing \square	1902 change on Form 9-330.)
MULTIPLE COMPLET	<u> </u>	† •
CHANGE ZONES		
ABANDON*		to the size
	nd Abandon Tocito Zone	
17. DESCRIBE PROI including estima measured and to	POSED OR COMPLETED OPERATIONS (Clearly stated date of starting any proposed work. If well is a rue vertical depths for all markers and zones pertine	te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*
	pulled 1 1//" tubing with seal	assy. Ran Baker Model
7-21-82 Pulled 1 1/4" tubing with seal assy. Ran Baker Model "C" Bridge Plug to 6800' with Packer set at 6600'. Squeezed Tocito Perforations 6730 to 6736 with 200 sacks Class "B" Cement containing .8% DGS, (Flater)		acker set at 6600'.
		30 to 6736 with 200
		ng .8% DGS. (Fl.10
		Loss Additive) Final pressure 3000#.
	Plug down 5:38 9 7-21-82.	
Tested 4 1/2 casing from 6600' to surface with		to surface with 2 2
		* defeat
		Set @ Ft
Subsurface Safety V	/alve: Manu. and Type	Set @ Ft
18. I hereby certify	that the foregoing is true and correct	
SIGNED COLE	e les 6. Orguetere Superinten	
-	GUEPICO FOR RECORD STATE	office use)
		DATE
APPROVED BYCONDITIONS OF APP	PROVAL, IF ANY:	
CONDITIONS OF AFT	AUG 04 1982	
	MONT DISTRICE	

BY FARING DISTRICT