

DEPARTMENT OF THE INTERIOR verse side  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Union Oil Company of California dba Unocal

3. ADDRESS OF OPERATOR

P.O. Box 850 Bloomfield, New Mexico 87413

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.  
At surface

Rincon 93 - 800'FSL & 1050'FEL

Rincon 94 - 800'FSL & 990'FWL

Rincon 231-1140'FSL & 970'FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

93-6517'DF 94-6525'DF 231-6516'GR

5. LEASE DESIGNATION AND SERIAL NO.

SF-079160

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NA

7. UNIT AGREEMENT NAME

Rincon Unit

8. FARM OR LEASE NAME

Rincon

9. WELL NO.

93PC, 231DK

10. FIELD AND POOL, OR WILDCAT

Pictured Cliff & Dakota

11. SEC., T., R., M., OR BLK. AND

Sec 11 T26N

Sec 22 T26 R7W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

RIPOUT OR ACIDIZE

REPAIR WELL

(Other) Install Cathodic Protection

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANT

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.

Proposed installation of cathodic protection to well casing:

Procedure: Drill a 6" diameter hole, 300 ft. deep within the existing well location boundary. Six Lida ST-1.60/50 anodes will be installed below the uppermost waterbearing formation, and back filled with coke breeze (99.5% carbon) to completely surround the anodes. Backfill rest of hole with gravel or drilling tailings.

A DC rectifier will be installed on the existing well location and a buried DC positive cable will be connected to the Lida ground bed from the rectifier. Negative DC cables from the rectifier will also be buried and connected to the well casings to be protected. These cables will be buried 18" to 24" deep in the middle of the road as shown on attached map. Therefore, an archaeological study will not be submitted because all work will take place on previously disturbed ground.

Unocal's completion expectation is by July 15, 1990.

ACCEPTED FOR RECORD  
FARMINGTON RESOURCE AREA

JUN 21 1990

Ken Townsend

FARMINGTON, NEW MEXICO  
DATE 03/05/1990

18. I hereby certify that the foregoing is true and correct

SIGNED

*Mike Sabert*

TITLE Production Technician

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCD

\*See Instructions on Reverse Side