

Form 9-331a  
(Feb. 1951)


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. SF 079035-A

Unit \_\_\_\_\_



SUNDRY NOTICES AND REPORTS ON WELLS **RECEIVED**

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	<input type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Sept. 26, 1955

Well No. D-204 is located 760 ft. from N line and 660 ft. from E line of sec. 9

C-13 (1/4 Sec. and Sec. No.) 264 (Twp.) 6W (Range) 34N (Meridian)

South Dakota (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the ~~derick floor~~ Ground above sea level is 6596 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a well as located above, to a depth of approximately 7800' to test the upper Morrison sands. This test will be drilled with rotary equipment.

Casing and cementing program as follows; 450' 10 3/4" casing with cement circulated to surface, 7800' of 7" OD 23# and 26# seamless casing cemented with 500 sacks cement.

This well shall be completed to produce through casing perforations and shall be fractured if necessary to obtain an economical and efficient rate of flow.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Lowry et al Operating Acct.

Address Box 967

Farmington, New Mexico

By Frank Gray  
Title Field Superintendent