

APPROVED APR 7 1955

A. P. Fleeman
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau 42-R388.1
Approval expires 12-31-52

Land Office Santa Fe
Lease No. 079161
Unit Candado

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Sand-Oil Treatment	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 25, 1955

Well No. 2 is located 990 ft. from N line and 990 ft. from E line of sec. 9

SE 1/4 Sec 9 26N 7W N.M.P.M.

South Blanco P.C. Rio Arriba New Mexico

The elevation of the derrick floor above sea level is 6105 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Moved in cable tools, pulled tubing, cleaned out to bottom.
Sand-oil treatment using 7,700 gallons diesel oil and 10,000*
sand, flushed with 2,300 gallons diesel oil. Interval treated
2205' to 2281'. Breakdown pressure from 1300* to 1100*.
Treating pressure maximum 1300*, minimum 1100*. Final pressure
500*. Injection rate 41.3 barrels per minute.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company CANDADO PRODUCTION COMPANY

Address 1400 LUMS TOWER

PHOENIX, ARIZONA

By George D. Locke
By Robert K. Green
Title President

