

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
JUL 2 1990

Sundry Notices and Reports on Wells OIL CON. DIV./

DIST. 3

1. Type of Well
GAS

2. Name of Operator
Meridian Oil Inc.

3. Address & Phone No. of Operator
Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec, T, R, M.
1650'S, 945'W Sec. 08, T-26-N, R-04W, NMPM

5. Lease Number
Jic Apache Cont #119

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Jicarilla 119 N 1

9. API Well No.

10. Field and Pool
Tapacitos Pic Cliffs

11. County and State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut Off

☐ Altering Casing

☐ Conversion to Injection

☐ Other

13. Describe Proposed or Completed Operations

5-18-90 MOL&RU. ND hanger, NU BOP. POOH w/108 jts 1 1/4" tbg & pkr. TIH w/RBP & fullbore pkr on 2 3/8" tbg. Set RBP @ 3325', set prk @ 3305'. Circ hole w/wtr. unable to locate csg failure.

05-19-90 POOH w/pkr. PT down csg. Load bradenhead w/5 BW. Retest csg, no flow from bradenhead. TIH w/pkr set @ 1621'. PT down tbg. Continue in hole w/pkr set @ 3305'. PT 775#/5 min, ok. Release RBP, reset @ 3414'. PT BP 1200#/5 min. PU RBP, reset @ 3325'. PT 1200#/5 min, ok. Made multiple tool setting, located csg failures 2887-56', 1959-28', and slight failure above 1928'. POOH w/pkr & tool. SDFN. (cont'd on back)

14. I hereby certify that the foregoing is true and correct

Signed Lois L. L. L. Title Regulatory Affairs Date 5-31-90

ACCEPTED FOR RECORD
JUN 01 1990

(This space for Federal or State office use)

FARMINGTON RESOURCE AREA

BY 201

APPROVED BY _____ TITLE _____ DATE _____
CONDITION OF APPROVAL, IF ANY: ENMOCC

05-20-90 TIH w/retrieving head & pkr. PU RBP @ 3325', tag fill @ 3464'. Reset RBP @ 3457'. PT BP 1250, ok. POOH w/pkr. Ran CBL log, TOC @ 2970'. SD for weekend.

05-22-90 Perf'd 2 squeeze holes @ 2890'. TIH w/pkr set @ 2696'. Spot 10 gal sand to cover RBP. Establish rate. Pump 75 sx Class "B" w/2% calcium chloride, displace 10.75 BW, hesitate & obtained 750 psi squeeze pressure. WOC. Work stuck pipe & pkr. SDFN.

05-23-90 Ran free point, tbg free @ 1980'. Made chemical cut on 2 3/8" tbg @ 1975'. POOH w/64 jts 2 3/8" tbg (23 jts fish). TIH w/shoe, wash pipe, jars, DC's on 2 3/8" tbg. Tag cmt @ 1928'. Wash over & cut cmt from 1928-2032'. Wash over 57' fish (127' wash pipe). TOOH. SDFN.

05-24-90 TIH, wash over from 2032-2044'. TOOH. TIH, wash over 2044-79'. TOOH w/10 std tbg. SDFN.

05-25-90 TOOH, wash over 2079-84'. TOOH. TIH, wash over 2084-88'. Pull wash pipe above fish to 1928'. SDFN.

05-26-90 TOOH w/tools. LD pipe. TIH w/overshot, tag & PU fish @ 1975'. Fish parted @ 2088'. TOOH w/113' of fish. SD for holiday

05-30-90 LD fishing tools & 108 jts 1 1/4" tbg. TIH w/2 3/8" tbg. SDFN.

05-31-90 Set 2 3/8" tbg @ 2085'. Mix 15 sx Class "B" w/3% calcium chloride, balance plug w/7.25 BW. LD 24 jts tbg. WOC. Tag cmt top @ 1870'. PT csg 500#, ok. LD tbg. Released rig.