



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079162
Unit NKL

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		<u>Subsequent Report of Workover</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 12th, 1956

Well No. 2-8 is located 1650 ft. from N line and 390 ft. from E line of sec. 7

NE/4 SE/4 Sec. 7 26N 7W M.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

South Blanco FC Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6106 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

12- 2-56 Moved in cable tools.
12- 3-56 Pulled tubing. Cleaned out to total depth.
12- 4-56 Sandfraced with 17,700 gallons water and 30,000# sand, flushed with 2,300 gallons water. Break-down pressure 1000#, treating pressure 750-1000#, average injection rate 42.3 barrels per minute.
12- 5-56 Cleaned out to total depth. After 15 hours flowing 3,477 MCF/day. Ran 73 joints 217' of tubing.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company KING-LOC PETROLEUM COMPANY

Address 716 First National Bank Bldg.

Phoenix, Arizona

By George D. Locke

Title Secretary-Treasurer