

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Contract 101

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lowe

9. WELL NO.

1.

10. FIELD AND POOL, OR WILDCAT

Tapacito Pictured Cliff

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11, T26N, R4W NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

1. OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

Consolidated Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

1860 Lincoln Street, Denver, Colorado 80295

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1850' FNL & 1450' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. It is proposed to plug and abandon the Lowe No. 1 (Pictured Cliff).
2. Cement perfs from 3822' to 3876'. Set cement retainer at 3700' and squeeze perfs with 150 sx. cement.
3. Perf two (2) squeeze hole at 3150' and attempt to squeeze with 75 sx. cement. Base Ojo Alamo approximately 3100'. If cannot break down assume Ojo Alamo covered with cement.
4. Perf at surface casing shoe and circulate cement to surface via 8-5/8" x 5-1/2" annulus. Leave both annulus and 5-1/2" casing full cement.
5. Install dry hole marker.



18. I hereby certify that the foregoing is true and correct

SIGNED

D. T. Stogner

TITLE Chief Drilling and
Production Engineer

DATE 1/18/78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

1973

OK