

COPY FOR
STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
SUBMIT IN TRIPPLICATE TO
DISTRICT OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079160
Unit 27 1/4 Sec. 12
Rincon Unit
I Sec. 916

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 19, 1953

Well No. 11 is located 1700 ft. from N line and 1800 ft. from E line of sec. 12

27 1/4 Sec. 12 (4 Sec. and Sec. No.) 26N (Twp.) 7W (Range) 111W (Meridian)
Blanco Arriba Canyon Dist. (Field) Alamo Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 4751 ft. UD

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Drill 13 3/4 inch Rotary hole to 110 foot. Set 100 feet of 10 3/4 inch surface casing. Circulate out with 100 sacks.

Drill 8 3/4 inch hole to 3100' or top of Pictured Cliff - set 20", 7 inch with 100 sacks regular cement.

Drill 6 inch hole with Calbe Tools from 3100 to 3200 foot.

Shoot open hole, tamped, with 300 quarts Nitro Gel.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ralph A. Johnston

Address Box 313

Farmington, New Mexico



James L. Copeland
Supt.