STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leskage tests In Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

ARRIBA PROD. MEDIUM (Tog. or Cog.) TBG. BG.
TBG. BG.
BG.
or No)
w No)
** ****
<u>-IN</u>
-IN
-IN
NG
NG
GOR
or No)

FLOW TEST NO. 2

PRESSURE

Zone producing (Upper er Lower):

1146	CAPSED TIME			→ PROD. ZONE	
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS
	1	į			
······································					
	1				
			<u></u>		
				1	
	 		ļ		
			1		
· ·	 				
	ļ, ,,,,		<u> </u>		
, .	•				
duction rate d	uring test				
	DOB!	D. 1		•	
	BOP	D based on	——— Bbls. in	Hours.	Grav GOR
		VCE			
		MCF	PD: Tested thru	(Orifice or Meter)	:
aele.					
					· · · · · · · · · · · · · · · · · · ·
					· *•
					*
rehv cerrify th	ar the informatio	n herein contains	ed is some and		of my knowledge.
icby certaly th	at the intolliant		ed to true and con	mpiete to the best	of my knowledge.
roved	Johnny Rolin	rown	10 C	\	CONOCO INC.
ew Mexico Oi	i Conservation D	ivision	/	perator	CONOCO INC.
		1 1	R	æ	11100011 1111 0 00
ļ	JUN 1 4 19	195	D		JUDSON VALDEZ
	L	1 1			
			T	itle	Field Operations Foreman
ใกเ	PUTY OIL & GAS IN	SPECTOR	T	itle	Field Operations Foreman
	PUTY OIL & GAS IN	SPECTOR			Field Operations Foreman

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A packer leakage test shall be commenced on each multiply completed well within ven days after actual completion of the well, and annually thereafter as prescribed by the der authorizing the multiple completion. Such tests shall also be commenced on all ultiple completions within seven days following recompletion and/or chemical or fracter treatment, and whenever remedial work has been done on a well during which the cker or the tubing have been distributed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

nced at flour, date) **

At least 72 hours prior to the commencement of any packer leakage test, the operator all notify the Division in writing of the exact time the test is to be commenced. Offset erators shall also be so notified.

The packer leakage test shall commence when both zones of the dual completion are ut-in for pressure stabilization. Both zones shall remain shut-in until the well-head essure in each has stabilized, provided however, that they need not remain shut-in more an seven days.

For Flow Test No. 1, one zone of the dual completion shall be produced at the normal re of production while the other zone remains shut-in. Such test shall be continued for ren days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack a pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be shut-in, in accornce with Paragraph 3 shove.

Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Tt No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).