


Section 8

(SUBMIT IN TRIPLICATE)

Land Office Santa FeLease No. 34-046Unit Cheney FederalUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	XX
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 15, 1956

Well No. 1 is located 990 ft. from N line and 990 ft. from E line of sec. 8S&T Section 8 26N 2E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Extension of Blanco Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 7215 ft. Est.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding, cementing points, and all other important proposed work)

6150' ID. Set 2301' of 5 1/2" Liner on bottom with 125 sx cement.
Top of liner 3849. Squeeze retainer @ 3816'. Squeeze top of
liner with 160 sx cement. Drilled cement in 7-5/8" to 3849'.
Drilled & washed out cement plugs to 6105 PBTD. Tested 5 1/2" liner
with 1500 Lbs. for 30 min. Tested OK. No break. Top of cement
by temperature survey @ 4270'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company MAGNOLIA PETROLEUM COMPANYAddress BOX 633MIDLAND, TEXASBy A.I. GERMAN
Title Division Superintendent