

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY


Land Office Santa Fe  
Lease No. S.V. 079162  
Unit \_\_\_\_\_

2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)



May 21, 1952

Well No. 6-13 is located 1020 ft. from N line and 360 ft. from E line of sec. 7

<u>N.L.</u> (¼ Sec. and Sec. No.)	<u>25 N</u> (Twp.)	<u>7 E</u> (Range)	<u>S.M.P.M.</u> (Meridian)
<u>S. Blanco</u> (Field)	<u>Nio Arriba</u> (County or Subdivision)	<u>New Mexico</u> (State or Territory)	

The elevation of the derrick floor above sea level is 6122 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Proposed Pictured Cliffs sandstone location.  
Probable total depth 2200 ft. Will set 120 ft. of 10 3/4"  
surface casing with cement circulated to surface. 2100 ft.  
or 5 1/2" production string cemented on top of Pictured  
Cliffs sandstone.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Kingsley-Locke Oil Co.  
Address 1400 Luhrs Tower  
Phoenix,  
Arizona  
By F. C. Barnes  
Title Geologist