(April 2003)					
			0		

(SUBMET IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

		5.00	300 32
	Market Street M.	- 40.50	
	Dadget Durchs M Applicat replies	7 E E	,
÷	التنافي المرابعية		unity of the
		77 YE	12.772
			47
	han April Jica	4.5	
		_	
	Ana	eka .	7
	Apa		
	Tribal	T.es	
	Anna Tribal		7Y-
			7.
		_	
	Costa	a <i>e</i> t 1	5.7
	Contri		-

NOTICE OF INTENTION NOTICE OF INTENTION NOTICE OF INTENTION	ON TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF REPORT OF REPORT OF ANABOSHOOT SUBSEQUENT REPORT OF ANABOSHOOT SUPPLEMENTARY WELL, HISTORY	
NOTICE OF INTENTS	OR TO ABANDON WELL	SEP 17 130P	
	(MOICHTE ABOVE BY CHECK M	MARK NATURE OF REPORT, NOTICE, OR OTHER BATA) U. S. GEOLOGICAL SURVEY	
		September FARMINGTON, NEW MEXICO	
	arilla -8 is located _1055 ft.	from [N] line and 1850 ft. from [E] line of sec. BI	
NE/4	8 26N	5W NMPM	
Basin Dak		o Arriba New Mexico	
Tapicito P	ctured Cliffs (O	lounity or Subdivision) (State or Tursbury)	
he elevation o	f the derrick floor above se	ea level is 6940 ft. Ground Level	
	•	ETAILS OF WORK	
itate memos of and (ing points, and	how alsoe, weights, and lengths of proposed ensings; indicate moudding jobs, course of all other important proposed work)	
undded at 8.	OO P. M. 7/14/63. D	Drilled 17" hole to 300'. Set 12-3/4" casing	
2001 KB 4	comented with 275 sa	icks of regular 2% CaCl ₂ . Cement circulated	
	(4.00 A M 7/16/63.	Drilled 11" hole to 4000'. Set 8-5/8" Casi	
lug down at	A'OO W TATE IL TOLOGE		
20001 757		racks of 50.50 Pownix and 90 sacks of regula	
: 3999' KB, ith 2% CaC		acks of 50-50 Pozmix and 90 sacks of regula 30 A. M. 7/25/63. Pressured to 1500 psi. h	
3999' KB, ith 2% CaC		racks of 50.50 Pownix and 90 sacks of regula	
: 3999' KB, ith 2% CaC		racks of 50.50 Pownix and 90 sacks of regula	
3999' KB, ith 2% CaC		sacks of 50-50 Pozmix and 90 sacks of regula 30 A. M. 7/25/63. Pressured to 1500 pai, h	
3999' KB, th 2% CaC		sacks of 50-50 Pozmix and 90 sacks of regular 30 A. M. 7/25/63. Pressured to 1500 pai. h REFERENCE SEP 1 9 196	
3999' KB, ith 2% CaCl	cemented with 134 solly. Plug down at 12:3	SEP1 9 196:	
3999' KB, ith 2% CaCl	cemented with 134 states of the states of the states of work must receive approximate this plan of work must receive approximate the	SEP 1 9 1963 OIL CON. CO	
: 3999' KB, ith 2% CaCl cay.	cemented with 134 solly. Plug down at 12:3	SEP 1 9 1963 OIL CON. CO	
3999' KB, ith 2% CaCl	cemented with 134 state of the consolidate of the c	SEP191963 OIL CON. CO U. & GAS. INC.	
ith 2% CaCl kay. Iunderstand the Company	CONSOLIDATED OU	SEP19196: OIL CON. CO. DIST. 2.	
ith 2% CaCleary. I understand the Company	cemented with 134 state of the consolidate of the c	SEP19196: OIL CON. CO DIST. 2 By ARRIVAL A	
t 3999' KB, ith 2% CaCl kay. I understand the Company	CONSOLIDATED OU	SEP19196: OIL CON. CO. DIST. 2.	