

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM 03381	
2. NAME OF OPERATOR Caulkins Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 780, Farmington, New Mexico		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 700 FNL and 1800 FNL, Section 7-26N-6W		8. FARM OR LEASE NAME Breach "B"	
14. PERMIT NO.		9. WELL NO. PD-123	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6680 GL 6692 KB		10. FIELD AND POOL, OR WILDCAT South Blanco Pictured Cliff	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 7-26N-6W	
		12. COUNTY OR PARISH Rio Arriba	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☒	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set DM Cement retainer at 6482 and squeezed perforations from 6797 to 6812 with 100 sacks ~~XXXX~~ neat cement containing .4% Halad 9 followed by 100 sacks neat. Perforations leaked after this squeeze, so another retainer was set at 6536 and perforations squeezed with 100 sacks neat cement containing .6% Halad 9, after which there was no leak.

Perforated with 4 holes at 3160, then set D ^{retainer} at 3030. Mid braderhead cement job with 100 sacks neat cement followed by 50 sacks latex cement. Squeezed with 100 sacks neat cement containing .4% Halad 9, then with 50 sacks neat. Final pressure 3000#. After drilling retainer and cement these perforations held 2000# pressure satisfactorily.

Drilled well with gas to 7590. Cemented 4 1/2" 10.5 and 11.6# J-55 casing at 7590 with 110 sacks cement (60 neat followed by 50 latex, all containing 12# gilsonite per sack). ran temperature survey and found top of cement at 6490. Cement will stand for 96 hours or longer before any further operations are started. Plug down at 11:00 PM, 8-18-64

18. I hereby certify that the foregoing is true and correct

SIGNED

Frank Brant

TITLE

Superintendent

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

U. S. GEOLOGICAL SURVEY

FARMINGTON, N.M.

DATE August 19, 1964

RECEIVED

AUG 21 1964

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.