Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE* Other instructions on reverse side) UNITED STATES

Form approved, Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SER AL NO.

GEOL	.OGICAL	SURVEY

Contract #97 6. IF INDIAN, ALLOTTEE OR TEIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) Jicarilla Apache 7. UNIT AGREEMENT NAME GAS WELL WE'L |X|OTHER 2. NAME OF OPERATOR 8. FARM OR LEASE NAME Consolidated Oil & Gas, Inc. Tribal "C" 3. ADDRESS OF OPERATOR 9. WELL NO. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface 9-A 10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde 1190' FSL & 1850' FEL 11. SEC., T., R., M., OR BLK. AND Sec. 7, T26N, R3W, NMP 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH | 13. STATE 6911! Gr. Rio Arriba New Mex. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL

TEST WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE ABANDON* REPAIR WELL CHANGE PLANS (Other)

FRACTURE TREATMENT ALTERING CASING SHOOTING OR ACIDIZING ABANDON MENT (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - 11-26-77: Drill 9 7/8" hole to 3922! KyB.
 - Ran 108 jts. 7 5/8" 33.7# (3910). Set at 3922 K.B. 11-27-77: Dowell cemented w/200 sx 65-35 poz 12% gel 1/4# Flocele/sx 100 sx C1 "B" 2% Cacl; 1/4# Flocele/sx. Plugged in 3:30 a.m. WOC 12 hrs. Test csg. 1000 psi. T.C. by temp. survey 2100'.
 - 11-30-77: Drilled 6 3/4" hole to 7406' K.B. Ran logs with Schl, Gamma Ray Ind., FDC & SNP
 - 12-1-77: Ran 5 1/2" 15.5# Liner 3606 & set @ 7387 Top liner @ 3781. Dowell cmtd. w/225 sx 50-50 poz 4% gel & 0.4% HR-4 & 10# fine Gilsonite/sx. Plugged down @ 3:15 p.m. Waiting on Completion Rig.

		DIST 3
8. I hereby certify that the foregoing is true and correct SIGNED	Sr. Drlg. Erigr.	DATE 126-77
(This space for Federal or State office bee)		
APPROVED BY	TITLE	DATE