

1-2-5255, Durango, Colo.

Form 9-331
May 1963

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. ST 079161
2. NAME OF OPERATOR Holm Oil Co.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 400, Antee, New Mexico 87410		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any requirements. See also space 17 below.) At surface Unit 0 Section 4 T 26 N R 7 W R14 Arroyo Co., N.M.		8. FARM OR LEASE NAME Camacho
14. PERMIT NO.		9. WELL NO. 3
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6161 GL		10. FIELD AND POOL, OR WILDCAT South Alamo FC
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 4-26N-7W
		12. COUNTY OR PARISH RA
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other)

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other)

REPAIRING WELL ☒
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Repaired leak in 3 1/2" csg.

7/25/75 - Set bridge plug @ 2150' GL.

7/26/75 - Holes in csg @ 1471' & 1975' GL.
Set packer @ 1430' & squeezed w/ 120 mm regular cement.

7/28/75 - Found another hole in csg @ 492'.

7/29/75 - Perforated 494' - 498' & 489' - 491' w/ 4 shots per/ft.
Squeezed w/ 60 mm regular cement.

7/31/75 - Drilled out cement 440' to 501'. Pressure test OK
Drilled out cement 1415' to 1581'. Pressure tests OK

8/ 1/75 - Drilled bridge plug & cleaned out to TD 2360' GL

8/ 2/ 75 - Ran 2 3/8" tbg. Set @ 2331' GL

RECEIVED

AUG 21 1975

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE **Production manager**

DATE **8/18/75**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting or any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.