

Well file

1-20-60

F. Loc. 660/S: 1980/W Elev. 6538 GL Spd. 100 Comp. 1-14-30 TD 6170 PB 100
 Casing S. 1-14-30 @ 100 W 300 Sx. Int. 7 @ 120 W 200 Sx. Pr. 1 @ 100 W 200 Sx. T. 2 3/4 @ 6707
 Csg. Perf. 6502-10, 6522-30, 6546-48 Prod. Stim. 100 T. SHL 0.1
925 PCF, 878 MCF - tested - 7-8-75
 BO/D 10-15-75
 I.P. 100 MCF/D After 24 Hrs. SICP 1350 PSI After 7 Days GOR 100 Grav. 1.0 1st Del. 5 25 0 s 50

TOPS		NITD	Well Log	TEST				DATA			
				Schd.	PC	Q	PW	PD	D	Ref. No.	
Kirtland		C-102	Plat ☒								
Fruitland		C-103	Electric Log ☒								
Pictured Cliffs		C-104	C-110								
Cliff House		1-15-76	3-122								
Menefee		Ditr	Dfa								
Point Lookout		Datr	Dac								
Mancos		Remarks <u>4 1/2 Cus. Pictured Cliffs - 5-22-75</u> <u>from 60 to 60 feet</u> <u>5-80</u> <u>160</u>									
Gallup											
Dakota											
Morrison											
Entrada											

P
 o Undes. Gal. RA 5 T 26N R 6W L N On Caulkins Oil Co. L 50 B Breech NE No. 102
 Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec.