

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Chalkins Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 780, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1880' F S/L and 1980' F E/L

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Plug Back ☒

5. LEASE

NM-03551

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Breech E

9. WELL NO.

587

10. FIELD OR WILDCAT NAME

Blanco-Mesa Verde

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA

Section 4 26N-6W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6440' Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-30-79

Plugged Back 6687 to 6460 with 35 sacks Neat cement.

Spotted 9.2# Gel Based Mud 6460 to 5716.

Spotted cement plug 5716 to 5420.

PBTD now 5420.

Subsurface Safety Valve: Manul. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Charles Dupre Mgr. Superintendent

8-9-79

(This space for Federal or State use only)

APPROVED BY
OPERATIONS OF APPROVAL, IF ANY

TITLE

DATE