This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

			147	MULINITIES .	11200 111					Well
marstor	Car	colidated 0	11 &	Gas Inc.		Le	ease_	He	yt	No. 1 (GD)
										- .
f Well.	Unit.	H Sec.	5 Tv	MD.	26	Rge	∍	4	County	RA
I Merr.	01120			1	LADE	e or rrou.	•	LIC OTION	OI IIOU.	
	N	ame of Reser	rvoir	or Pool		L or Gas)	<u>(</u> F	low or	Art. Lift)	(Tbg. or Csg.)
oper					Ì					
ompletio	n (lellup		·	ic i	1		Flew		Tbg
ower										
ompletio	n I	Daketa	_		Ga	ાક		Flow		Tog
<u> </u>				PRE-F	LOW SI	HUT-IN PR	ESSUF	RE DATA		1.01-2-23-2-20
pper Hou	ır, da	te		Length	of			SI pres		Stabilized?
omol S	Shut-i	n 7-15-69				7 Days		psig	97/9	(XXXXX No) Stabilized?
ower Hou	ır. da	te		Length	of	f		SI press.		
ompl S	Shut-i	n 7-15-69		time shu	t-in	7 Days		psig	637	(XEXXX No)
					FL	OW TEST N	<u>0. T</u>	l é		WYENT OWO !
ommenced	at (hour, date)		-22-48					roducing (Xpp)	EXPERIENCE).
Time		Lapsed time	i	Pres				d. Zone		narks
hour, da	ite)	since*	Uppe	r Compl.	Lowe	r Compl.	Ter	mp •	nen-	MIKS
7-36-68	3	4 Days		1002		442				
		_		200		101				
7-39-68	3	7 Days	ļ	1006	<u> </u>	434	+			
					1		1			
			4	· · · · · · · · · · · · · · · · · · ·	ļ		 			
			+		 		+			
			+		1		+			
			1							
		- duning to			L			,		
roduction	on rat	te auring ce	വൈർ	on		Bbls. in		Hr	s. Gr	avGOR
)11:	120	BOFD C	MCEPI	· Tested	thru	(Orifice	or M	eter):	Meter	avGOR
as:	HZU									
Upper Ho	ur de	at e		Length	of			SI pre	55 •	Stabilized?
Compl	Shut.	in 7-15-5 8	t	time sh	ut-in	21 Day	·s	psig	1008 ss.	(XEEX OF NO)
Lower Ho				Length	of			SI pre	88•	Stabilized?
Compl	Shut -	in 7-29-68	<u>}</u>	time sh	ut-in	7 Day	<u> </u>	psig	<u>\$50</u>	(YESKET No)
o o mp = 1					FI	LOW TEST !	<u>vo. 2</u>	<u>}</u>	777	I
Commence	d at	(hour, date	\ ₩₩	9-5-	68			Zone p	roducing (upp	er brokkner).
Time		Lapsed time		Pressure			Prod. Zone		roducing (Upper protects): Remarks	
(hour. d	ate)_	since **	Uppe	er Compl.	Lowe	er Compl.	- 1	'emp.	ne	IIIGI RO
				_			1			
8-9-48		4 Days		456		<u> 394 </u>				
					1					
8-12-4	8	7 Days		43Q		930	-			- COST CONTRACT
			1							- / KLLITYER
		<u> </u>								
										AUG 9 0 100
					+				 	1 - 6 1988
					1					OIL CON COM.
										DIST COM.
					1					3/
<u></u>	<u>-</u>									
Producti	ion ra	te during t	est bossi	020		Bhla, in	÷	Hrs.	. Grav.	GOR
0il:		BOPD	Daseu	DD 4 Togte	d thm	u (Orific	e or	Meter)	Meter	
Gas:		7 .7	PIOT	ID, 1660e	, U 1111	u (01_11=0	• ••			
REMARKS:	:	····	-							
		10- 1b-1 1b	- 1-6	ormetion	harai	n contain	ed 1	s true	and complete t	to the best of my
		LIY CHAT CH	אווד בא	AT WOOD AT ANY						
knowledg	_		J	, .	e i Posta	Opera	tor	Can	salidated Oil	& Gas Inc.
		8	-2	6 19/	8	opos.			4	,
Approved	a:	Oil Conserva	tion	Commission	on .	Bv 4	Cli	nle	Dhe	liss
New Me	xico (OTT Conserva	OTOW	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	P	<u>ئـــ</u> رد		1	V	
D	//	2. K.	111	de la la		Title	, <i>O</i>	Pros	do etien S oneri	eligs intendent
מ - רבים Pi	ETROL	EUM ENGINE	ER DIS	T. NÖ, 🕱		Date		Ausr	ust 21 1968	
TITTE										

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

 DAKOTA PRESSURES

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Commission on Northwest New Mexico Packer Leakage Test Form Revised 11-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form.