



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____

Sierrita

Allottee Contract # 128

Lease No. _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 4, 1956

Well No. Y-2-2 is located 200 ft. from N line and 1000 ft. from E line of sec. 8

11 1/4 11 1/4 8
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat-Sabota, Blaine Elizaville
(County or Subdivision)

NY State W-110000-20.

The elevation of the surface above sea level is 6000.0 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TO 7000'. RUN 7000'. The 1 1/2" casing was perforated from 7000-00, 7010-00, 7020-00, 7030-00 and the Sabota form fractured in 4 stages. Days after clean out the NY. Prepare to set a temp SP @ 5400', selectively perforate the 1 1/2" casing & fracture the Sabota formation in four stages. Set temp SP @ 3800', perforate the 7-8/8" casing & fracture the PG formation. Drill out temp SP & clean out to 70. Set Baker pump on wire line above the Sabota formation @ approx 7400'. Set 2-7/8" @ taking @ 7400' w/mud pump above the NY formation @ approx 4800'. An Otto side door choke will be run below the anchor pump @ approx 4800'. 1 1/2" tubing will be run inside the 2-7/8" tubing & set in the side door choke @ 4800' w/a pack off to separate the 1 1/2" tubing from the 2-7/8" tubing annulus, thereby allowing the Sabota formation to flow thru the 1 1/2" tubing and the NY to flow thru the 1 1/2" x 2-7/8" tubing annulus. A second string of 1 1/2" tubing will be run inside the 2-7/8" tubing & 7-8/8" casing (see back).

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Northwest Production Corporation

Address 200 Sioux Building
Albuquerque, New Mexico

RAY PHILLIPS
Ray Phillips

By _____

Title Asst Mgr, Production Operations

amounting to a depth of approx 2100' to produce the 1C formation. A dual-stage
core, arranged to obtain specimens on all these formations, will be used.
The 1/2 of the 5, containing 110.70 cores, is dedicated to this well and the
formation; the 11/4, containing 100.70 cores, is dedicated for the
shots and plotted 11110 formations.