2_

COPY TO O.C.C.

P. O. Bex 965 Farmington, New Mexico

December 6, 1955

Candado Production Company 1400 Luhrs Tower Phoenix, Arisona

Re: Santa Fe 079161

Gentlemen:

Receipt is acknowledged of your "Notice of Intention to Drill" dated December 2, 1955 covering your well No. 11 Candado in NE's ME's sec. 3, T. 26 N., R. 7 W., N. M. P. M., Rio Arriba County, New Mexico, South Blanco P.C.

Tour proposed work is hereby approved subject to compliance with the provisions of the "Oil and Gas Operating Regulations" revised May 25, 1942, a copy of which will be sent to you on request, and subject to the following conditions:

- Drilling operations so authorised are subject to the attached sheet for general conditions of approval.
- 2. Furnish copies of all logs.

Very truly yours,

(Orig. Sgd.) P. T. McGRATH

P. T. McGrath District Engineer

PTMcGrath:ac



х

(SUBMIT IN TRIPLICATE)

Land Office	Santa	Fe
Lease No	07916	<u> </u>

UNITED STATES

UNITED STATES

Unit NE/4 Sec. 3 is

DEPARTMENT OF THE INTERIOR Designated Drilling Unit

GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR ACIDIZING SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	December 2, 1955
NE/4 NE/4 Sec. 3 26N (1/4 Sec. and Sec. No.) (Twp.)	from $\begin{Bmatrix} N \\ X \end{Bmatrix}$ line and 900 ft. from $\begin{Bmatrix} E \\ XW \end{Bmatrix}$ line of sec. 3 7W N.M.P.M. (Range) (Meridian) Arriba New Mexico (State or Territory)
(Co	unty or Subdivision) (State or Territory)
The elevation of the derrick floor above see	a level is 6583 ft. G.L.
	TAILS OF WORK
State names of and expected depths to objective sands; sho ing points, and	ow sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- d all other important proposed work)
Pictured Cliffs Sand tes	st. Estimated total depth 2850'.
Surface Casing: 95' of with 80 the sur	8-5/8" OD 24# J-55 casing cemented sacks, or sufficient to circulate rface.
Production " : Approxi casing	imately $2780'$ of $5-1/2"$ OD $14\#$ J-55 cemented with 100 sacks.
If commercial production will be shot with nitrog	is indicated, the producing section slycerin and/or sand-oil treated.
I understand that this plan of work must receive approx	val in writing by the Geological Survey before operations may be commenced.
Company CANDADO PRODUCTION C	OMPANY
ddress 1400 LUHRS TOWER	
PHOENIX, ARIZONA	By

Title Secretary

X

<u> 2</u> (3.4. 1.4)

 $0 \leq 0 \geq 1.00$, $0 \leq 0 \leq 0.00$, $0 \leq 0.00$

that a constraint of the \mathbb{R}^2 is the \mathbb{R}^2 to \mathbb{R}^2 . The figure is a small constraint of the first of the firs

The state of the

 $(A_{ij}(z) \otimes x^{ij}) = (A_{ij}(x) \otimes x^{ij}) \otimes (A_{ij}(x) \otimes x^{ij})$

1,410,011

Candade			Well 20.//		
T. 26 H R 7 W N.M.P.M.					•
900 feet fre	m morth	line; {	000 1	eet We4	fre
	verag in	one Ba		,	
n: 6583 GL.					
Arriba County	No	w Mexic	3.0		
				900	
			1	70	
SI SI	SCTION 3				
			 		••••
		 			
				+	
				\perp	

STEPHEN H. KINNEY
Registered Professional
Engineer and Land Surveyor

Surveyed November 29

Seal:

MEXIC