NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

<u></u>			EW MEXICO PACK			Well
· ————			Le			
cation	· A Sec. 3	Two. 2/2	Rge	• 6. 14	Count	y RA
Well. Onle	, <u>/21</u>		Type of Prod.	Method	of Prod.	Prod. Medium (Tbg. or Csg.)
1	Name of Reserv	oir or Pool	(Oil or Gas)	(Flow or	Art. Lift)	(Tbg. or Csg.)
	sa Verde		Gas		OW	Tubing
wer De	leate		Gas	רא	.OW	Tubing
wer Da	.kota				OW	1401116
			LOW SHUT-IN PRE	SSURE DATA SI pres		Chabilined?
pper Hour, date			Length of			Stabilized? (Yes or No)
ompl Shut-in			time shut-in			Stabilized?
ower Hour, date			Length of time shut-in			(Yes or No)
mpl Shut-				psig		
mmonood at	(hour date)*	8:30 AM	9-13-77	Zone pr	oducing (Upr	er or Lower):
Time	Lansed time	Press	sure	Zone producing (Up		
our date)	since*	Upper Compl.	Lower Compl.	Temp.	Remarks	
8:30 AM	9200					
	24 hrs	380	411		Bc	oth zone shut in
9-14-77 8:30 AM						
9-15-77	48 hrs	380	425		Di	itto
8:30 AM						
9-16-77	72 hrs	381	441	<u>_</u>	W Shut In	Dakota opened
8:30 AM				-		
9-17-77	24 hrs	395	237	ļ	Dá	akota flowing
8:30 AM			00/		. ה	:
9-18-77	48 hrs	395	226		Ditto	
pper Hour, date Length of			of	ESSURE DATA SI pres psig	press. Stabilized?	
Compl Shut-in			time shut-in		ss.	Stabilized?
Lower Hour, date Compl Shut-in			Length of time shut-in			(Yes or No)
ompi Snuc-	-TU	1 CIME SITU	FLOW TEST N			
ommenced at.	(hour, date)	- 		Zone p	roducing (Up	per or Lower):
Time	Lapsed time	Pres	sure	Prod. Zone		
	since **	Upper Compl.	Lower Compl.	Temp.	R	emarks
				-		
				; 		
	<u></u>					
				!		•
	 					
	+					
		ĺ				
				i i		
			<u></u>	<u> </u>	<u> </u>	
roduction ra	ate during te	st .	m 7 ·	17	Cmar	, GOB
)il:	BOPD ba	ased on	Bbls. in	Hrs.	Usav	GOR
as:		_MUFPU; Tested	i thru (Orifice	or Meter):		
TWADEC -						
(EMARAS:				_ 		
hanshy car	tify that the	information	herein contain	ed is true a	and complete	to the best of my
mowledge.					1	
MANAGE .	O TOO	1977	Opera:	tor <u>Caul</u> k	ins Oil Co	mpany
oproved:	OCT 3	/				
New Mexico	Oil Conservat	ion Commissio	n By	By Chaile Vergues		
				Super	intenden#	•
Зу	1 E Mayer	Ill &	Title	T		
			D_1 -	Q- 3 ∩	.77	
Title	The second second second	•	∪at€	7-70-	11	

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- 2. At least 72 hours prior to the commencement of any packer leakage test the operator shall notify the Commission in criting of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both hongs of the deal completion are shut-in for pressure stabilization. Both nones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than beyon days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-on. Such test shall be continued for seven days in the case of right seven and for 24 hours in the case of an only well. Sole if the an initial garder leakage test, a gas well is being flower to TITE almosphere due to the large of a pipeline connection the flow period shall be treed modes.
- Following completion of Flow Test No. . . the *E | set. . again to show in, in accordance with Paragraph 3 above
- 6. Flow Test No. 2 shall be conditted ever though no heak was indicated during Flow Test No. 1. Procedure for him less No. 1 is to be the state as for Flow Test No. 1 except that the procedure produced none chall cumulan shut-in while the zone which was previously shut-in is produced.

- Concreased pressure seals must be measured on each zone with General pressure gauge of time intervals as follows: 3-hour tests, immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oli or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as leguired above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 mays after completion of the test. Tests shall be filed with the acted District Office of the New Mexico Oil Conservation Commission on Noticewest New Mexico Packer Leakage Test Form Revised 11-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures find more only, and gravity and SCR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the record of the Packer Leakage Test form.

