(April 1952)							
			, e				
ļ							

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Approval expin	es 12-81-60.
Indian AgencyJi	carilla-
Apache	
Allottee Socon	y-Mobil
Cont	ma at 07

NOTICE OF INTENTION TO DRILL		SUBSEQUENT RE	PORT OF WATER SHUT-OF	F	_ X_
NOTICE OF INTENTION TO CHANGE PL	ANS	SUBSEQUENT RE	PORT OF SHOOTING OR A	CIDIZING	
NOTICE OF INTENTION TO TEST WATER	1		PORT OF ALTERING CASIN		
NOTICE OF INTENTION TO REDRILL OF	R REPAIR WELL	N	PORT OF REDRILLING OR	REPUBLIC G	看到 图 [1]
NOTICE OF INTENTION TO SHOOT OR			PORT OF ABANDONMENT_	IN I	
NOTICE OF INTENTION TO PULL OR AL	i	SUPPLEMENTAR	WELL HISTORY	<u> </u>	1 23 1962
NOTICE OF INTENTION TO ABANDON V	ÆU			יטעו	
(INDICATE	ABOVE BY CHECK MARK N	ATURE OF REPORT, N	OTICE, OR OTHER DATA)	n cen	LOGICAL SURVEY
·				U. S. GEO	TON NEW MEXICO
			November 21	FAU.000	962
Tribal		(A.T)	nc.	1	•
Well No. 7-5 is loca	ated 890 ft. from	$n \begin{Bmatrix} N \\ S \end{Bmatrix}$ line and	_890_ft. from \(\frac{\cappa_0}{\sqrt{3}} \)	line of sec	
		(22 J		,	,
NE 5	26N (Twp.)	(Range)	NMPM (Meridian)		
4.		(Mexico	
Blanco Mesaverde		r Subdivision)		or Territory)	-
Tapicito Pictured Clif		1. 71116.		•	•
The elevation of the derrick	floor above sea lev	el 18 m	•		
	DETAIL	LS OF WORK	•		•
•	objective sands; show size	s, weights, and lengt	he of proposed casings; ind	icate mudding jobs	, cement-
(State names of and expected depths to		1			
(State names of and expected depths to	ing points, and all ot	her important prop	peed work)		
		•			
Drilled to 4020'. Ra	ın 7-5/8" 26.4	1 lb. J-55	casing to 4019'	. Cemente	ed
Drilled to 4020'. Ra	n 7-5/8" 26.4	1 lb. J-55 169 cu. ft.	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Ra	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	lb. J-55 169 cu. ft. mix cement	casing to 4019' Diacel "D", fo	. Cemente	ed h
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and	n 7-5/8" 26.4 r cement with 97.5 sx. Pozi	1 lb. J-55 169 cu. ft. mix cement ob held.	Diacel "D", for with 4% gel,	. Cemente	ed h g,
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and gas drilled below cas	nn 7-5/8" 26.4 r cement with 97.5 sx. Poznsing, cement jo	1 lb. J-55 169 cu. ft. mix cement ob held.	Diacel "D", for with 4% gel,	Cemente ollowed with Drilled plu	ed h g,
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and gas drilled below cass I understand that this plan of work Company Consolida	r cement with 97.5 sx. Pozz sing, cement jo	1 lb. J-55 169 cu. ft. mix cement ob held.	Diacel "D", for with 4% gel,	Cemente ollowed with Drilled plu	ed h g,
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and gas drilled below cas	r cement with 97.5 sx. Pozz sing, cement jo	1 lb. J-55 169 cu. ft. mix cement ob held.	Diacel "D", for with 4% gel,	Cemente ollowed with Drilled plu	ed h g,
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and gas drilled below cass I understand that this plan of work Company Consolida	r cement with 97.5 sx. Poznesing, cement journal in ted Oil & Gas.	1 lb. J-55 169 cu. ft. mix cement ob held.	Diacel "D", for with 4% gel,	Cemente ollowed with Drilled plu	ed h g,
Drilled to 4020'. Rawith 75 sx. of regula 97.5 sx. regular and gas drilled below cass I understand that this plan of work Company Consolida Address 2150 E. Mex	r cement with 97.5 sx. Poznesing, cement journal in ted Oil & Gas.	1 lb. J-55 169 cu. ft. mix cement bb held. writing by the Gook	Diacel "D", for with 4% gel,	Cemento ollowed with Drilled plu	ed h g,