

5 USGS 1 McHugh 1 NWP& 1 File

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)approved,
District Bureau No. 42-R1424.

5. LEASE ORIGINATOR AND SERIAL NO.

Cont. #120

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Undes. Gallup

11. SEC. T. R. M. OR BLK. AND

SURVEY OR AREA

Sec. 30, T26N, R4W NMPM

1.

OIL
WELL ☐GAS
WELL ☐

OTHER

Dry Hole

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

930 Petroleum Club Bldg, Denver, Colo.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1640' fnl 820' fel

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

6760' RKB

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

11/5/68

M.O.C. Spudded 12 1/4" hole @ 11:30 P.M., 11/4/68 - Drilled to 205'
ran 7 fcs. @ 5/8" O.D., 240, LR, STAC csg. T.E. 235.31' set @ 200' RKB,
cemented with 155 ex. Class "B" plug 21' csgl. P.O.B. 5:15 A.M., 11/5/68,
cement circulated.

11/15/68

T.D. 7075' Driller. 7085' Logger. Ran Haller E.S. Induction and
Gamma Ray Density logs. Plugged well as follows: 30 ex. 6600' - 6500',
30 ex. 5600' - 5500', 30 ex. 4775' - 4675', 30 ex. 3325' - 3225', 30 ex.
2920' - 2820', 10 ex. surface plug. Rig released 5:00 A.M., 11/19/68.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 12/9/68

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

DEC 12 1968

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.