

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR  
Consolidated Oil & Gas, Inc.3. ADDRESS OF OPERATOR  
1860 Lincoln Street, Denver, Colo 802954. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 790' FWL & 1850' FNL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

## SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐5. LEASE  
Contract #1016. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Huron

9. WELL NO.  
#1-A

10. FIELD OR WILDCAT NAME

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 2, T26N, R4W NMPM

12. COUNTY OR PARISH 13. STATE  
Rio Arriba New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6924' Cr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-31-78: MOL &amp; RU Spud 15" Surface hole 12:00 Midnight

2-1-78: Drilled 15" hole to 294' - Fluid level @ 70' K.B.  
Ran 7 jts. 10 3/4" 32.75# H-40 ST&C. Set @ 286' K.B. - Cement  
w/175 sx Cl "B" w/2% cc & 1/2# Celloflake/sk. P.D. 7:00 p.m. -  
Cement did not circ - Cement down top side to 70' K.B. w/225 sx  
Cl "B" w/3% cact<sub>2</sub> & 1/2# Celloflake/sk - Cement circ. WOC 12 hrs.

2-2-78: Test 10 3/4" csg. to 800 psi 1/2 hr. O.K.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Veryl Moore TITLE Foreman DATE 2-9-78  
Veryl Moore

(This space for Federal or State office use)

APPROVED BY TITLE DATE  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side