

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Consolidated Oil &amp; Gas, Inc.

3. ADDRESS OF OPERATOR

1860 Lincoln St., Denver, Colo 80295

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1060' FEL &amp; 1850' FNL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: 6450'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐

SUBSEQUENT REPORT OF:

☒☐☐☐☐☐☐☐☐

5. LEASE

Contract #119

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hoyt

9. WELL NO.

#3-A

10. FIELD OR WILDCAT NAME

Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 5, T26N, R4W NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7290' GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-16-78 Drilled 8 3/4" hole - 4325'. Ran 425.01' of 29# LT&amp;C N-80, 2622.50' of 26# LT&amp;C N-80, 1281.18' of 23# LT&amp;C K-55 Total of 4418.04' of 7" csg.

Set @ 4324' K.B.

Cmt'd. w/150 sx 65/35 poz, 12% gel &amp; 100 sx C1 "B" Neat 2% Calc 1/4#

Cellflake/sx. P.D. @ 4:30 AM 4-16-78. WOC 12 hrs.

Top of Cement by Temp. survey 1900'.

4-17-78 Air drilled 6 1/8" hole - 6450'. Ran ID Gamma Ray &amp; FDC log - Ran 2256' 4 1/2" 10.50# K-55 STC liner and set @ 6450' K.B. F.C. 6405' K.B. Top of liner 4136' K.B. Cmt'd w/250 sx 50/50 poz w/4% gel &amp; 10# fine Gilsonite/sk w/0.4% HR-4 P.D. to 6223' @ 8:15 PM 4-19-78.

WO Completion Rig.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED: *Leo Carr*

TITLE Prod. Supervisor

DATE 4-21-78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

State  
COPY TO ROSWELL