

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 03554
2. NAME OF OPERATOR Caulkins Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 780 Farmington, New Mexico		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 930' from the North and 930' from the East		8. FARM OR LEASE NAME Breech "C"
14. PERMIT NO.		9. WELL NO. 744
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6616 Gr		10. FIELD AND POOL, OR WILDCAT South Blanco PG
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 14 26N 6W
		12. COUNTY OR PARISH Rio Arriba
		13. STATE N Mex

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud 5:15pm 7-22-78

Drilled 12 1/4" hole to 102'.


Cemented 8 5/8" 24# J-55 new casing at 102' with 125 sacks 2% CaCl.

Plug down 1:30am 7-23-78

Cement circulated to surface.

Tested surface casing 7-24-78 with 500# for 30 minutes.

No decrease in pressure.



18. I hereby certify that the foregoing is true and correct

SIGNED Dwight Blumett

TITLE Prod. Foreman

DATE 7-25-78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

\*See Instructions on Reverse Side

RECEIVED  
AUG 2 1978