

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
CONSOLIDATED OIL & GAS, INC.

3. ADDRESS OF OPERATOR
P.O. BOX 2038, FARMINGTON, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1190' FNL - 790' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

AUG 05 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug & Abandon well as follows:

Set plug @ 5584.44' - 5447' w/10 sx cmt
Set plug @ 3929.82' - 3577' w/67 sx cmt
Set plug @ 3384' - 3282' w/21 sx cmt
Perf 7" csg w/4 shots @ 342' Set plug from surface
and circulate cmt out Braiden head
Install P & A Marker

RECEIVED

JAN 16 1985

OIL CON. DIV.

DIST @ 3

Ft.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Benny Jones TITLE Drilling Foreman DATE July 30, 1982

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
AS AMENDED

DEC 13 1984

John Miller
MILLENBACH
AREA MANAGER

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side

OPERATOR