

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Consolidated Oil & Gas, Inc.

3. ADDRESS OF OPERATOR
1860 Lincoln St., Denver, Colo 80295

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1190' FNL & 790' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐

☐

☐

☐

5. LEASE
Contract #97

6. IF INDIAN, ALI OTTEE OR TRIBE NAME
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Tribal

9. WELL NO.
8-7-R

10. FIELD OR WILDCAT NAME
Tapacito Pictured Cliff
Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 5, T26N, R3W NMPM

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7109' Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
SEP 15 1978
OIL CON. COM.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 8-23-78 MI & RU Spud time 1:00 pm 8-23-78
8-24-78 Drilled 15" hole 300'. Ran 7 jts. 10 3/4" 40.5# K-55 ST&C csg. 280.40'. Set @ 292.40' K.B. Cemented w/300 sx Cl "B", 2% Cacl, 1/2# Cellflake/sk. Cmt. Circ. P.D. 8:30 p.m. WOC 12 hrs. Test csg. to 800# psi. OK
Drilled 8 3/4" hole to 4093'. Ran 7" 23# K-55 csg. 4119' K.B. Cmt'd. w/150 sx 65-35 poz w/12% gel & 100 sx Cl "B" Neat w/1/2# Cellflake & 2% c.c. WOC 12 hrs. B.P. w/1500# Held OK 12:30 8-28-78
8-31-78 Drilled 6 1/2" hole 6220'. Dresser Atlas ran ID-Gamma Ray & FDC logs. Ran 60 jts. 4 1/2" 10.50# K-55 ST&C csg. 2150.34' F.C. @ 6139' K.B. Top of liner 4009' K.B. Cmt'd. w/250 sx 50/50 poz w/4% gel, 4/10 of 1% FLA & 6 1/2# fine Gilsonite/sk. Bumped the plug w/2500# @ 8:30 p.m. 8-31-78.
WO Completion Rig.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Vern Moore TITLE Prod. Foreman DATE 9-8-78
Vern Moore

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

DURANGO OFFICE COPY

*See Instructions on Reverse Side