

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
Box 3249 Englewood, Co 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 835' FWL 930' FNL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Recompletion activities (subsequent)

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☒  
☐  
☐  
☐

5. LEASE

09-000110

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla Dulce, NM

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Jicarilla A

9. WELL NO.  
9

10. FIELD OR WILDCAT NAME  
Mesaverde/Chacra

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 20 T26N R5W

12. COUNTY OR PARISH  
Rio Arriba

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6695' gr

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/25/80 TIH w/2-3/8" tbg and land open ended @ 3867', w/SN 1 jt above 3835'.  
ND BOP. NUWH. Opened well to pit. RDMOSU. SITP: 750 PSI. SI to build pressure  
overnite.  
10/4/80. MIRUSU. TOH w/tbg. TIH w/bottom hole assy, tagged sand @ 4771'. Clean  
out 179' of sand to pkr. Landed 2-3/8" Mesaverde production string in Baker model  
D production pkr @ 4950'. Bottom of muleshoe is @ 4961' w/sn @ 4908. Blast  
joints across Chacra. ND BOP NUWH. Retrieved circulating plug. Opened Mesaverde  
to flow to pit.

\* Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Asst. Div. Adm. Mgr. DATE January 28, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: