UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF TH GEOLOGICAL S		Jicarilla Apache Tribal Cont. 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND R	EPORTS ON WELLS	Jicarilla Apache 7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to eservoir. Use Form 9-331-C for such proposals. 1. oil gas 🕥)	8. FARM OR LEASE NAME Jicarilla 152W
well well other 2. NAME OF OPERATOR		9. WELL NO. 4A
EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR POR SOLUTION AND ADDRESS OF OPERATOR		So. Blanco P.C. and Blanco M.
BOX 990, FARMINGTON, NE 4. LOCATION OF WELL (REPORT LOCA below.)		11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA Sec. 55, T-26-N, R-5-W
AT SURFACE: 1760'N, 1185' AT TOP PROD. INTERVAL:	W	12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INITERPORT, OR OTHER DATA	DICATE NATURE OF NOTICE,	14. API NO.
·	SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD 6557' GL
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	⊠ □ □	
REPAIR V/ELL PULL OR ALTER CASING		(NOTE: Report results of multiple completion or zon change on Form 9–330.)
MULTIPLE: COMPLETE CHANGE ZONES CHANGE ZONES		
17. DESCRIBE PROPOSED OR COMPLE including estimated date of starting measured and true vertical depths for	any proposed work. If well is d	te all pertinent details, and give pertinent dates directionally drilled, give subsurface locations and nt to this work.)*
Ran 5 ioints	Drilled surface ho 9 5/8", 32.3# H-40 s	surface casing 206' set at 220'.
Circulated to	o surtace. WUC 12 no	ours; held 600#/30 minutes.
		a properties of the properties
Subsurface Safety Valve: Manu. and Type		Set @ F
18. I hereby gertify that the foregoing is t		
SIGNED Al & Brises	TITLE Drilling Cler	rk
	(This space for Federal or State of	ffice use)
APPROVEC BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE

*See Instructions on Reverse-Side

WILSON SERVICE COMPANY TEMPERATURE SURVEY COMPANY E1 Paso Natural Gas Co. WELL 4-A LEASE Jicarilla 152 W COUNTY Rio Arriba STATE New Mexico SEC = 5 TWP. 26 RGE 5 APPROX. TOP CEMENT 2700' Survey Begins at 1500' Ft. Ends at 3414' Approx. Fill-Up Max. Temp. Log Measured From KB Run No. Casing Depth Diam of Hote to 84" from Casing Size Depth 7" . from to from to Date of Cementing 7/24/78 Time 5:30 AM 7/24/78 Time 1:30 PM Date of Survey Amount of Cement55 Scks 65/35 Class B with 6% Gel Flake + 27 Ca Cl. + 100 Scks Class B with 2% Ca.Cl. Recorded by Hunter Witnessed by REMARKS OR OTHER DATA Float Valve @ 3439' TEMPERATURE IN DEGREES FAHRENHEIT 3200°

3200°

3200°

3200°

3200°

FORM 432-2