UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	Contract No. 103
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEORGAIONE GONTEI	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas 🗷 other	Jicarilla "H"
Well Other	9. WELL NO.
2. NAME OF OPERATOR	11
Supron Energy Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota - Blanco Mesaverde
P.O. Box 808, Farmington, New Mexico	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA Sec. 18, T-26N, R-4W
AT SURFACE: 1450 ft./N;790 ft./W line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above.	Rio Arriba New Mexico
AT TOTAL DEPTH: Same as above.	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6781 G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ' TEST WATER SHUT-OFF \[\bigcap \]	→ c
FRACTURE TREAT	
SHOOT OR ACIDIZE	소통량하는 중요 출연원진
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
CHANGE ZONES	그 그는 전 시 회원들은 사회 학회 원이 용사
ABANDON*	ଓ ଅନୁଧାର ଜଣ ଅନ୍ତର୍ଶ ହେଉଛି ।
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	
including estimated date of starting any proposed work. If well is dismeasured and true vertical depths for all markers and zones pertinent	rectionally drilled give subsurfees leasting and
We originally filed to complete this well onl	y in the Dakota zone. We
now propose to complete it as a Dakota - Mesa	
have been filed with the New Mexico Oil Conse	
offset operators have been notified. The Dak	ota will be perforated
from 7676 ft. to 7822 ft. and sand - water fr	
of 20-40 sand and 52,500 gallons of 1% Kcl wa	
will be perforated from 5083 ft. to 5839 ft.	
with 72,000 lb. of 20-40 sand and 72,000 gall	ons of 1% Kcl water.
	OTVITION OF THE PROPERTY OF TH
	2 0 1979 IIIN 2 0 1979
Subsurface Safety Valve: Manu. and Type	THE TUNKS OF
·	Set @ OIL CON. 60M
18. I hereby certify that the foregoing is true and correct	pist. 3
SIGNED Kenneth E. Roddy TITLE Production Sup	
(This space for Federal or State office	e use)

DATE ,

_ TITLE .

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: