UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	Contract No. 150
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas 🖼	Jicarilla, "G"
well well well other	9. WELL NO.
2. NAME OF OPERATOR	4- A ₹
SUPRON ENERGY CORPORATION	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Mesaverde
P.O. Box 808 Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA N.M.P.M.
below.)	Section 11; Twp. 26N, Rge. 5 West
AT SURFACE: 790'f/North and 790'f/West line. AT TOP PROD. INTERVAL: Same as above.	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH: Same as above.	Rio Arriba New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
REFORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7251 KDB
TEST WATER SHUT-OFF \[\bar{\bar{\bar{\bar{\bar{\bar{\bar{\b	
RACTURE TREAT	ာကု မြောက်သည်။ မြောက်သည်။ မြောက်သည်။
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9–330.), ඉන්නය සි දීම්වීම පිදුවිදිය දී
CHANGE ZONES	
ABANDON*	
other)	선물 기를 받는 사람들이 되었다.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and	
measured and true vertical depths for all markers and zones pertinent	t to this work.)* 영요설립한 및 무료및 문
1	Section 1997
1. Spudded hole at 9:45 p.m. 9-13-78.	흥성통합니다. 등 소리통합
2. Drilled 13-3/4" hole to T.D. of 233 feet.	
	# # # # # # # # # # # # # # # # # # #
3. Ran five joints of 10-3/4", 32.75#, H-40 casing landed at 233 feet.	
4. Cemented w/150 sacks of class "B" w/2% Calcium Chloride.	
Plug down at 2:45 p.m. 9-14-78. Cement circulated to surfaces	
	三
	FIFT DOUGTE COM
	TEA IS COLD 3
Subcurface Safety Valvey Many and Type	Elite Manager
Subsurface Safety Valve: Manu. and Type	Set @
8. I hereby certify that the foregoing is true and correct	
IGNED Middle Matt TITLE Area Superintendent 10-10-78	
Rudy D. Motto	
(This space for Federal or State offic	e use)
PPROVED BY TITLE	DATE SELECTION OF THE PROPERTY OF THE PROPERT
CONDITIONS OF APPROVAL, IF ANY:	· · · · · · · · · · · · · · · · · · ·
	조상 열뚝시하면 1972 현