OIL CONSERVATION DIVISION

Page Revised 10/01/7

This form is not to be used for reporting packer leskage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	UN:	UNION OIL COMPANY OF CALIFORNIA Lease RINCON UNIT					No			
Location of Well:	Unit M	Sec12		Rge	7W		Cou	nty R	RIO ARRIBA	
		NAME OF RESERV	DIR OR POOL	TYPE OF F			ETHOD OF PROD (Flow or Art. LIN)		PROD, MEDIUM (Tbg. or Cag.)	
Upper Completion	BL/	ANCO MESA VI	RDE GAS FLOW				TUBING			
Lower Completion	DACTH DAVOTA			GAS	GAS		FLOW		TUBING	
			PRE-FLO	W SHUT-IN P	RESSURE	DATA				
Upper Completion	1.43444			Days		Tbg 1090			bilized? (Yes or No) Yes	
Lower Completion		t 12, 1995	Length of time shu 8:00am	7 Days .	21 bless bak		Thg 1880 No			
				FLOW TEST	NO. 1					
Contimenced	i at (hour, dal	•• August :	00am	7	Zone producing (Upper or Lower): Lower					
TIME LAPSED TIME (hour, date) SINCE#		PRESSURE Upper Completion Lewer Completion		PROD. ZONE TEMP.		REN	REMARKS			
10:00		1 Hr.	Csg 1090 Tbg 1090	Tbg 580	63		Q = 73	O MCF/	D	
11:00	am	2 Hrs.	Csg 1090 Tbg 1090	Tbg 500	63	۰	Q = 730 MCF/D		D	
		Csg 1090 Tbg 1090	Tbg 500	63	0	Q = 730 MCF/E		D		
•				·		•			·	
								==		
Production	on tate di	uring test							,	
Oil:		BOP	D based on	Bbls. in	ı	_Hours.	G	12v	GOR	
Gas: MCFPD; Tested thru (Orifice or Meter):										
MID-TEST SHUT-IN PRESSURE DATA										
Upper Completion	Hour, date at Augus	t 18, 1995	Length of time shut 12:00pm	n Days	SI press. psig	Csg I Tbg 1		Stabilized?	(Yes or Ho) NO	
	Hour, date si		Length of time shut	-	SI press. paig			Stabilized?	(Yes or Ho)	
					<u> </u>					

(Continue on reverse side)



OIL COM. DIV.

FLOW TEST NO. 2

ommenced at (hour, date)** August 24, 1995 12:00pm				Zone producing (Upper or Lowert: Upper		
TIME	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE		
(hour, date)		Upper Completion	Lower Completion	TEMP.	REMARKS	
1:00pm	1 Hr	Csg 900 Tbg 620	Tbg 2290	67°	Q = 200 MCF/D	
2:00pm	2 Hrs.	Csg 750 Tbg 540	Tbg 2290	67°	Q = 200 MCF/D	
3:00pm	3 Hrs.	Csg 600 Tbg 400	Tbg 2290	67°	Q = 200 MCF/D	

VII	BOPD based on	Bbls. in	Hou rs.	Grav	GOR
Gas:	МСР	PD: Tested thru (Orid	fice or Meter):		
Remarks:	API #30-039-25489	·····			-

Approved	gel	my Robinson	1	9	Operato	
New Mexic	o O# Čo∏ī	servation Division]		_	
		AUG 3 0 1995			Ву	
Bv					Title _	
	DEPU	TY OIL & GAS INSPEC	TOR			
Tide					Date _	

Operator	Union Oil Company of California dba	Jnoc
Ву	R.L. Caine	
	Production Foreman	
Dete	August 28, 1995	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization: Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test 'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing a temperatures (gas zones only) and gravity and GOR (oil zones only).