

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Merrion & Bayless

3. ADDRESS OF OPERATOR

P.O. Box 1541, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2300 FNL and 750 FEL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spud, cement

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM-04073

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hill

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 30, T26N, R2W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7447 ft. GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-01-78 Set 225 ft. of 8-5/8", 24 lb./ft., J-55 casing at 237 ft. with 180 sax cement w/3% CACL. Plug down @ 12:15 a.m., 12-01-78.

12-11-78 TD and logging at 6200 ft.

12-12-78 Ran 6202 ft. of 4-1/2", J-55, 9.5 lb./ft. and 10.5 lb./ft. production casing and set at 6219 ft. KB. Dowell cemented first stage with 285 sax Class H with 50/50 Pozmix 2% gel, 10# gilsonite per sax 1/4# celaflake per sax 10 bbl. C/W 100 preflush. Opened Dowell stage tool at 3920 ft. KB and circulated 3.5 hrs. Cemented second stage with 215 sax Class H 65/36 Pozmix with 6% gel, 10# gilsonite per sax 14# celaflake. WOCT.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Co-Owner DATE 12-20-78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: