Form 9-331		••••				/	
(May 1963)	ay 1963) UNITED STATES SUBMIT IN TRIPLICAT					Form approved.	
DEPARTMENT OF THE INTERIOR (Other instructions on in					Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.		
			/				
	CHINIDDA M		6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
(Do not	SUINDAT IN	OTICES AND RE	PORIS O	IN WELLS		120 CK INIBE NAME	
(Use "APP	LICATION FOR PERMIT-	-" for such pro	ck to a different reservoir.			
1.					7. UNIT AGREEMENT	N. Ca	
WE'L	WELL X OTHE	CR.			THERE ASSESSED.	NAME	
2. NAME OF OPE	RATOR	8. FARM OR LEASE N					
Southlar	d Royalty C	ompany				1	
3. ADDRESS OF O	PERATOR	Tapacitos	9. WELL NO.				
P. O. Dr	awer 570, F						
4. LOCATION OF	WELL (Report locati	#2					
See also space At surface	17 below.)	10. FIELD AND POOL, OR WILDCAT					
4	1545' FSL	Wildcat					
	TO40 LOP	11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA					
14. PERMIT NO.		1 15			Section 25,	T26N, R2W	
14. PERSIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)		r, GR, etc.)	12. COUNTY OR PARIS	H 13. STATE	
			723' GR		Rio Arriba	New Mexic	
16.	Check	Appropriate Roy To	Indicata Na	ture of Notice, Report, or (0.1 0		
			malcale 140	ture or 14ofice, Report, or	Jiher Data		
	NOTICE OF IN	NTENTION TO:		SUBSEC	UENT REPORT OF:		
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF X					REPAIRING WELL		
FRACTURE TR	FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT				7		
SHOOT OR AC	SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING				ALTERING		
REPAIR WELL CHANGE PLANS (Other)					ABANDONM	ENT.	
(Other)					of multiple completion letion Report and Log for	on Well	
17. DESCRIBE PROP	OSED OR COMPLETED	OPERATIONS (Clearly state	all pertinent				
proposed we nent to this	ork. If well is dir work.)*	ectionally drilled, give sub	surface location	details, and give pertinent dates as and measured and true vertic	al depths for all marke	rs and zones perti-	
						÷.	
2-3-79	Set cemer	nt retainer at S	2440' 5	micored off Diames a		•	
	from 8480	Set cement retainer at 8440'. Squeezed off Burro Can				ions	
	from 8480' to 8489' with 35 sacks of Class "B" cement of cement on top of plug.				nt. Dumped 2	sacks	
	or caucin	- on cop or prug) -				
2-8-79	Sot gamer	ot votoinou at (T001 a				
2-0-19	OANNI to	or recamer at 6	590° S	queezed off Dakota	perofations fr	om	
	0400° to	8400' to 8409' with 35 sacks of Class "B" cement.					
			•				
						•	
					<u>.</u>		
					n _ 1		
				1170	Mark .		
	(Approved verbally by Ed Sabmidt 2_9_70)				e de la companya de l		
						1 6	
	(whhroveo	Approved verbally by Ed Schmidt 2-8-79)				31 3	
					- 1 6697 T	90%. I	
					A But the state of	3/	
18. I hereby certif	that the foregoing	gis true and correct					

TITLE .

(This space for Federal or State office use)